



A brand of **TOTAL**

# EVOLUTION 900 SXR 5W-40



**Very high performance lubricant based upon ELF synthetics technology, designed for lubricating all Diesel car engines.**

## APPLICATIONS

- All Diesel engines, especially those of recent technology**
  - Recommended for all supercharged or naturally aspirated Diesels in cars and light vans.
- Even in very severe conditions**
  - Suitable for all types of service (urban, or on the highway or motorway) especially in very severe conditions.
- Fast driving**
  - For all types of driving, especially at high speed.
- All times of year, even the coldest weather**
  - Specially designed to meet the demands of the motor manufacturers as regards extended oil-change.

Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer

## PERFORMANCES

- International specifications**
  - ACEA A3/B4
  - API: SM/CF
- OEMs approvals**
  - RENAULT 2.2 dCi DPF
  - RN0710, RN0700 : gasoline, turbo gasoline and Diesel without Diesel Particulate filter,

## CUSTOMER BENEFITS

- Best possible performance**
  - Excellent engine protection, particularly against wear in the timing system.
- Excellent engine cleanliness and protection**
  - Ensures an exceptionally clean engine.
- Easier starting in very cold conditions**
  - Outstanding thermal stability and oxidation resistance, guaranteeing that the oil will not degrade even in conditions of very severe use.
- Longer engine life**
  - Immediate lubrication of engine components during cold starts, leading to longer engine life.
- Extended oil-change intervals**
  - Lubricant performance sustained over time for extended oil change intervals.

## CHARACTERISTICS

	Method	Units	SAE Grade 5W-40
Density at 15°C	ASTM D1298	kg/m <sup>3</sup>	855
Viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	90
Viscosity at 100°C	ASTM 445	mm <sup>2</sup> /s	14,7
Viscosity index	ASTM D2270	-	172
Pour point	ASTM D97	°C	- 42
Flash point	ASTM D92	°C	230
B.N.	ASTM D2896	mgKOH/g	10

The typical characteristics mentioned represent mean values