TOTAL CLASSIC 5W-40





"TOTAL CLASSIC, the guaranteed quality"

Synthetic technology multigrade oil for gasoline and diesel engines, formulation using a set of additives with carefully selected performance and proportions to answer to the quality standards of the Association of the European Manufacturers.

APPLICATIONS

All Gasoline/Diesel engines Direct injection Diesel

The most severe journeys All times of year

"Vigorous" driving

- Recommended for all Gasoline engines (multivalve, turbocharged, with or without catalytic converter) and all Diesel engines with or without turbocharging in cars and light vans
- Suitable for all journeys (in town, on highways and motorways) and particularly in severe conditions
- For all driving styles, particularly "vigorous" and high speeds.

Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer.

PERFORMANCES

International Specifications

ACEA A3//B4 API SL/CF

CUSTOMER BENEFITS

High performance

Excellent engine protection, particularly against timing system wear

Lengthens engine life

• Immediate lubrication of engine parts during cold starts, leading to longer engine life

Extended oil change intervals

• TOTAL CLASSIC 5W-40 meets the requirements of the manufacturers as regards extended oil change intervals.

CHARACTERISTICS

TOTAL CLASSIC 5W-40	Units	SAE Grade
		5W-40
Density at 15°C	kg/m³	853
Viscosity at 40°C	mm²/s	85
Viscosity at 100°C	mm²/s	14
Flash point Cleveland	°C	228
Pour point The typical characteristics mentioned represent mean values.	°C	- 39

TOTAL LUBRIFIANTS 562, Avenue du Parc de l'île 92 029 Nanterre Cedex 1/1

TOTAL CLASSIC 5W-40 Sheet updated : 01/11 Sticker reference: MPC 11/2006

