PERFORMANCE SUPER D 15W-40

A brand of TOTAL

Mineral lubricant for diesel engines, suitable for on-road applications.

APPLICATIONS

- ELF PERFORMANCE SUPER D 15W-40 is a **mineral** lubricant for **on-road diesel** applications.
- It is recommended for **previous Euro 3 engine generations**.

APPROVALS

Specifications	API CG-4/SJ	ACEA E2
Manufacturers' approval	Mack EO-L MAN 271 MB-Approval 228.1 Volvo VDS	

PERFORMANCES AND CUSTOMER BENEFITS

- ELF PERFORMANCE SUPER D 15W-40 retains **excellent viscosity stability** in service, ensuring efficient engine lubrication engine in severe conditions.
- **Detergent, antioxidant and anti-corrosion additives** help to reach **standard oil drain intervals**.
- **Detergent, dispersant and anti-wear properties** keep the **engine clean** enable efficient control of soot, sludge and piston deposits.

PHYSICAL AND CHEMICAL CHARACTERISTICS

ELF PERFORMANCE SUPER D 15W-40		Method	Value
Density at 15°C	kg/m^3	ASTM D1298	887
Kinematic Viscosity at 40°C	mm^2/s	ASTM D445	101
Kinematic Viscosity at 100°C	mm^2/s	ASTM D445	14
Viscosity Index	-	ASTM D2270	141
Flash point	°C	ASTM D92	226
Pour Point	°C	ASTM D97	-33
T.B.N	mgKOH/g	ASTM D2896	8.5
Sulphated Ash	% m/m	ASTM D874	1.2

The features mentioned above are average values obtained with some variability in production and do not constitute a specification.

TOTAL LUBRIFIANTS
562 avenue du Parc de l'Ile
92029 Nanterre
FRANCE

afaq ISO 9001 Qualité AFNOR CERTIFICATION

This lubricant does not cause adverse health effects when used in the intended application.
A safety datasheet, is accessible on request from your local dealer.