



A brand of **TOTAL**

## SPORTI TXI C3 5W-30



**High performance lubricant using ELF synthetic technology, intended for lubricating all Gasoline and Diesel car engines. Specially formulated to ensure compatibility with DACIA post-treatment systems (after July 2011)**

### APPLICATIONS

**All Gasoline and Diesel engines, particularly those of recent technology**

- Recommended for all recent engines, multivalve, and turbocharged, direct injection, with or without catalytic converter.

**Varied to severe journeys**

- Particularly adapted to recent DACIA diesel equipped with a **post-treatment** system (DPF).

Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer

### PERFORMANCES

**International specifications\***  
\*check your drivers manual for OEM recommendation

ACEA C3

API SL/CF

### CUSTOMER BENEFITS

**A better environment protection**

- Enables the optimization of post-treatment that enables high reduction of pollutant emissions (Nox, CO<sup>2</sup>, CO) thanks to low rates of sulfur, ashes and phosphorus (low SAPs).

**Extended oil change intervals**

- Meets the most demanding OEMs requirements enabling extended oil change intervals (20000 km), thanks to an outstanding oxidation resistance.

- Gives the engine an excellent wear protection, thanks to its very solid additive package and adapted viscosity.

**Excellent engine protection and cleanliness**

- Ensures maximum engine cleanliness, thanks to very good detergent and dispersion properties.

### CHARACTERISTICS

|                    | Method     | Units              | SAE Grade 5W-30 |
|--------------------|------------|--------------------|-----------------|
| Viscosity at 40°C  | ASTM D445  | mm <sup>2</sup> /s | 69              |
| Viscosity at 100°C | ASTM 445   | mm <sup>2</sup> /s | 12              |
| Viscosity index    | ASTM D2270 | -                  | 171             |
| Pour point         | ASTM D97   | °C                 | - 36            |
| Flash point        | ASTM D92   | °C                 | 230             |
| B.N.               | ASTM D2896 | mgKOH/g            | 7               |

The typical characteristics mentioned represent mean values