

Safety Data Sheet

Product name :

CALORIS MS 23

Page : 1/6

SDS n° :30580-44

Version :1.00

Version of :2006-02-09

This sheet supersedes the one dated :2006-02-09

PRODUCT LABELS

LABELLING (standard or EU):

Not concerned

R-phrases :

None

S-phrases :

None

TRANSPORT LABELLING:

Not applicable.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY UNDERTAKING

Name of the product :

CALORIS MS 23

Code No. :

10S

Product application :

Lubricating grease

Supplier :

TOTAL UK LIMITED
40 Clarendon Road
Watford, Hertfordshire, WD17 1TQ
UNITED KINGDOM
Tel: 01923 694000
Fax: 01923 694400

*Contact :

Specific Product Related Info: 01977 636200

*Emergency telephones :

UK -
01923 694000

*Poisons Advice Centre :

NHS Direct: 0845 46 47 / Textphone: 0845 606 46 47

*Burns Units :

NHS Direct: 0845 46 47 / Textphone: 0845 606 46 47

See local details at end of sheet :

Manufacturer :

TOTAL UK LIMITED
40 Clarendon Road
Watford, Hertfordshire, WD17 1TQ
UNITED KINGDOM
Tel: 01923 694000
Fax: 01923 694400

2. HAZARDS IDENTIFICATION

*Health effects :

Under normal conditions of use, the product holds no danger of intoxication

Environmental impact :

Do not discharge this product into the environment.

Physico-chemical hazards :

No specific risk of fire or explosion under normal conditions of use

3. COMPOSITION/INFORMATION ON INGREDIENTS

PREPARATION

Chemical nature :

The product is made from refined mineral base oils and synthetic oils in which the polycyclic aromatic hydrocarbons (PCA or P14) content, measured by IP 346, is less than 3%.

Substances presenting a health hazard	EC No.	CAS No.	Content	Symbol(s)	R-phrases
Alkylated diphenylamines	270-128-1	68411-46-1	<2,4 %	N	R-51/53
propylene carbonate	203-572-1	108-32-7	<1 %	Xi	R-36

Safety Data Sheet

Product name :

CALORIS MS 23

Page : 2/6

SDS n° :30580-44

Version :1.00

Version of :2006-02-09

This sheet supersedes the one dated :2006-02-09

See section 16 for explanations of R-phrases :

4. FIRST AID MEASURES

IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.

Inhalation :	Inhalation of heavy concentrations of vapour, fumes or spray, may cause mild irritation of the throat. Transport the person into fresh air, keep warm and allow to rest.
Ingestion :	Possible risk of vomiting and diarrhoea. Do not induce vomiting to avoid the risk of aspiration into the respiratory tract.
Skin contact :	Immediately remove all soiled or stained clothing. Wash the affected area immediately and repeatedly with soap and water. If the skin is exposed to high-pressure spray, the product may enter the human body. In all such cases the affected person must be taken to hospital, even if no sign of injury can be detected.
Eye contact :	Keep eyes open and rinse immediately and repeatedly with water for at least 15 minutes.

5. FIRE FIGHTING MEASURES

Flash point:
See heading 9

Extinguishing media :	- suitable: Foam, carbon dioxide (CO ₂), powder. - not recommended: do not use water jets (stick jets) for extinguishing fire since they could help to spread the flames.
Specific hazards :	Incomplete combustion and thermolysis produce gases of varying toxicity such as CO, CO ₂ , various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled.
Protective measures for firefighters :	Insulated breathing apparatus must be worn in confined premises with heavy concentrations of fumes and gases.
*Other :	All combustion residues and contaminated water from fire-fighting should be disposed of according to local regulations.

6. ACCIDENTAL RELEASE MEASURES

See sections 8 and 13.

*Personal protection :	Ensure good ventilation. Remove sources of ignition. Do not smoke.
After spillage / leakage :	- On the soil: Surfaces on which the product has been spilled may become slippery. Do not allow the product to enter sewers or rivers or contaminate the soil. Recover with mechanical means such as pumps and skimmers. Contain and collect the spilled product with sand or any other inert absorbant material. In case of spillage, contact the competent authorities if the situation cannot be brought under control rapidly and efficiently. - On water: Floating absorbant material, then mechanical recovery. If the product is spilled in a river or in the sewers, notify the authorities of the possible presence of surface effluent.

Safety Data Sheet

Product name :

CALORIS MS 23

Page : 3/6

SDS n° :30580-44

Version :1.00

Version of :2006-02-09

This sheet supersedes the one dated :2006-02-09

7. HANDLING AND STORAGE

HANDLING :

Prevention of user exposure :

Ventilate extensively if the formation of vapours, fumes, mists or aerosol is a risk.
Make all the necessary arrangements in order to reduce exposure risk, notably to products in use or to wastes.
Keep away from combustible substances; keep away from food and beverages.

Prevention of fire and explosion :

Empty containers may contain flammable or explosive vapours.
There is a fire hazard associated with rags, paper or any other material used to remove spills which become soaked with product.
Avoid accumulation of these: they are to be disposed off safely after use.

Precautions :

Avoid static electricity build up with connection to earth.
Set up machinery and equipment so as to avoid the risk of accidental spills or splashes onto hot machine parts and electrical contacts (on joint failure, for example).

STORAGE :

Technical measures :

Make the necessary arrangements to prevent water and soil pollution.

Storage precautions :

- Suitable:
Store at room temperature, protected against contact with water and moisture, and away from any source of ignition.
Keep containers closed when not in use
- To be avoided:
Do not store exposed to the elements.

Incompatible products :

Dangerous reaction with strong oxidizing agents.

Packaging materials :

- Recommended:
Use only hydrocarbon-resistant containers, joints, pipes, etc.
Keep in original container if possible.
Otherwise, transfer all indications on the regulatory label to the new container.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Technical measures :

Use the product in a properly ventilated atmosphere.
When working on enclosed place (tanks, reservoirs...), make sure that atmosphere is not suffocating and/or wear recommended equipment.

*Respiratory protection :

It is not necessary in normal conditions.
In case of vapours or sprays formation:
Combined gas cartridge (organic gases and dust, filter A/P2).

Hand protection :

Impermeable hydrocarbon-proof gloves.
recommended material: nitrile , neoprene.
The demands on the gloves are determined by the conditions in practice (e.g. multiple use, mechanical load, temperature, strength and duration of exposition).
Before choosing suitable gloves, it is recommended that the user tests the gloves.
The break through times of the same type of glove of different manufacturers can be very different - even if the layer thickness is similar. Therefore the break through times have to be found out from the manufacturer of the protective gloves themselves.

Eye protection :

Goggles, in case of risk of splashing.

Skin and body (other than the hands) protection :

As required, wear a face mask, hydrocarbon-proof clothing, and safety boots (when handling drums).
Don't wear rings, watches or anything similar which can retain the product and may give rise to skin conditions.

Safety Data Sheet

Product name :

CALORIS MS 23

Page : 4/6

SDS n° :30580-44

Version :1.00

Version of :2006-02-09

This sheet supersedes the one dated :2006-02-09

Hygienic work practices :

Avoid prolonged and repeated contact with the skin, especially with used or waste product
Immediately remove all soiled or stained clothing.
If the product comes into contact with the skin, wash the affected area immediately and copiously with soap and water.
Do not use abrasives, solvents or fuels.
Do not use cloths stained with the product to dry hands.
Do not put the product-soaked rags into the pockets of working clothes.
Do not eat, drink or smoke while handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance :

Pasty

Colour :

Black or brownish-black

Odour :

Characteristic

Density/specific gravity :

880 kg/m³
Temperature (°C) 20

Température d'auto-inflammation :

> 350 ° C (ASTM E 659)

Comments on autoignition temperature :

This temperature may be significantly lower under particular conditions (slow oxidation on finely divided materials...).

Comments on explosivity :

Not applicable
Drop point: > 300 ° C (NF T 60-102)

Solubility :

- in water :
Insoluble and immiscible.
- in organic solvents :
Soluble in many common solvents.

10. STABILITY AND REACTIVITY

Stability :

The product is stable at normal storage, handling and use temperatures.

Conditions to avoid :

Heat, sparks, ignition points, flames, static electricity.

Materials to avoid :

Avoid contact with strong oxidizers

Hazardous decomp. products :

Incomplete combustion and thermolysis produces potentially toxic gases such as CO, CO₂, various hydrocarbons, aldehydes and soot.

11. TOXICOLOGICAL INFORMATION

Acute toxicity / Local effect :

Inhalation, comments:

Risk is improbable under normal conditions of use
Inhalation of high concentrations of vapour or aerosols may cause irritation of the upper respiratory tract.

Skin contact, comments:

Risk is improbable under normal conditions of use.
If the skin is exposed to high-pressure spray, the product may enter the body. In all such cases the affected person must be taken to hospital, even if no sign of injury can be detected

Ingestion, comments:

In case of ingestion of small quantities, no important effect observed. in case of ingestion of larger amounts: abdominal pain, diarrhea, ...

CHRONIC TOXICITY OR LONG-TERM TOXICITY :

Skin contact :

Characteristic skin affections (oil blisters) may develop following prolonged and repeated exposure through contact with stained clothing

Safety Data Sheet

Product name :	CALORIS MS 23	Page : 5/6
SDS n° :30580-44	Version :1.00	Version of :2006-02-09
This sheet supersedes the one dated :2006-02-09		

Sensitization :	To our knowledge, the product does not cause aggravated sensitivity.
-----------------	--

12. ECOLOGICAL INFORMATION

Comments about ecotoxicity :	Experimental data on the finished product are not available. It is considered to present a little danger for aquatic life. no information available for used product
Mobility :	- Air: there is a slow loss by evaporation. - Soil: Given its physical and chemical characteristics, the product has no soil mobility. - Water: The product is insoluble; it spreads on the surface of the water
Persistence and degradability :	No experimental information about the finished product. However the "mineral oil" fraction of the new product is intrinsically biodegradable.

13. DISPOSAL CONSIDERATIONS

Waste disposal :	Dispose of in a safe manner, in accordance with local regulations. If need be, collection by an authorised waste contractor and regeneration or incineration at an approved installation.
Waste class :	The waste classification mentioned here represents only a recommendation. The waste producer is responsible for the correct specification of the waste. The specification of the waste classification should be in arrangement with the authorised waste disposal company. The waste classification is dependant on the composition of the product at the time of disposal. 12 01 12
Disposal of contaminated packaging :	Proceed in compliance with the prevailing regulations.

14. TRANSPORT INFORMATION

Road (ADR) / Rail (RID) :
Transport by barge (ADNR) :
Marine (IMO-IMDG) :
Air (ICAO/IATA) :

15. REGULATORY INFORMATION

Not applicable	
Risk phrases :	None
Safety phrases :	None
EU directives :	Hazardous preparations directive 1999/45/EC modified (Directive 2001/60/EC).

16. OTHER INFORMATION

HSE Infoline: 08701 545500 / Minicom: 02920 808537
This sheet is in compliance with the standards defined by the directives 91/155/CEE, 93/112/CEE, 2001/58/CE and the article 14 of the directive 1999/45/EC.

Explanations of R-phrases in section 2 :	R-51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R-36 Irritating to eyes.
--	---



Safety Data Sheet

Product name :

CALORIS MS 23

Page : 6/6

SDS n° :30580-44

Version :1.00

Version of :2006-02-09

This sheet supersedes the one dated :2006-02-09

*Revision date: 2006-02-09

*Supersedes the data sheet of: 2006-02-09

* Information revised since the previous version of the SDS :

Safety Data Sheet status : Approved.

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.