

Product name: NEVASTANE SL 100 Page: 1/6

SDS n° :33841-44 Version :1.00 Version of :2004-11-30

This sheet supersedes the one dated :2004-06-21

PRODUCT LABELS

LABELLING (standard or EU): Not concerned

R-phrases: None S-phrases: None

TRANSPORT LABELLING: Not applicable.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY UNDERTAKING

Name of the product: NEVASTANE SL 100

Code No.: JFC

Product application: Oil for the food industry

Product in compliance with NSF-USDA-H1 requirements.

Lubricant for accidental food contact.

Supplier: TOTAL UK LIMITED

40 Clarendon Road

Watford. Hertfordshire. WD17 1TQ

UNITED KINGDOM Tel: 01923 694000 Fax: 01923 694400

*Contact: Specific Product Related Info: 01977 636200

*Poisons Advice Centre: NHS Direct: 0845 46 47 / Textphone: 0845 606 46 47

*Burns Units: NHS Direct: 0845 46 47 / Textphone: 0845 606 46 47

See local details at end of sheet:

Manufacturer: TOTAL UK LIMITED

40 Clarendon Road

Watford. Hertfordshire. WD17 1TQ

UNITED KINGDOM Tel: 01923 694000 Fax: 01923 694400

2. HAZARDS IDENTIFICATION

Health effects: Under normal conditions of use, the product holds no danger of intoxication

Environmental impact: Do not discharge this product into the environment.

Physico-chemical hazards: No specific risk of fire or explosion under normal conditions of use

3. COMPOSITION/INFORMATION ON INGREDIENTS

PREPARATION

Chemical nature: The product is made from synthetic base oils (Polyalfaolefins).

Substances presenting a health hazard	EC No.	CAS No.	Content	Symbol(s)	R-phrases
Alkylamine phosphate		80939-62-4	<0,5 %	Xi ,N	R-36/38, 51/53
N-phenyl-1-naphthylamine		90-30-2	<0,5 %	Xn	R-22, 43

See section 16 for explanations of R-phrases:



Product name: NEVASTANE SL 100 Page : 2/6

SDS n° :33841-44 Version :1.00 Version of :2004-11-30

This sheet supersedes the one dated :2004-06-21

4. FIRST AID MEASURES

IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.

Inhalation: Inhalation of heavy concentrations of vapour, fumes or spray, may cause mild

irritation of the throat.

Transport the person into fresh air, keep warm and allow to rest.

Ingestion: Possible risk of vomiting and diarrhoea.

Do not induce vomiting to avoid the risk of aspiration into the respiratory tract.

Give nothing to drink

Skin contact: Immediately remove all soiled or stained clothing.

Wash the affected area immediately and repeatedly with soap and water. Remove most of the product with a soft tissue and rinse with water.

Eye contact: Keep eyes open and rinse immediately and repeatedly with water for at least 15

minutes.

Aspiration: If the product is believed to have entered the lungs (in case of vomiting, for

example), take the person to hospital for immediate care.

5. FIRE FIGHTING MEASURES

Flash point: See heading 9

Extinguishing media: - suitable:

Foam, carbon dioxide (CO2), powder.

- not recommended:

do not use water jets (stick jets) for extinguishing fire since they could help to

spread the flames.

Specific hazards: Incomplete combustion and thermolysis produce gases of varying toxicity such as

CO, CO2, various hydrocarbons, aldehydes and soot. These may be highly

dangerous if inhaled.

Vapours can build explosive mixtures with air.

Vapours are heavier than air and may spread on the ground to sources of ignition.

Protective measures for firefighters: Insulated breathing apparatus must be worn in confined premises with heavy

concentrations of fumes and gases.

Other: All combustion residues and contaminated water from fire-fighting should be

disposed of according to local regulations.

6. ACCIDENTAL RELEASE MEASURES

See sections 8 and 13.

Personal protection: Ensure good ventilation.

Remove sources of ignition. Do not smoke.

After spillage / leakage : - On the soil

Surfaces on which the product has been spilled may become slippery. Do not allow the product to enter sewers or rivers or contaminate the soil.

Recover with mechanical means such as pumps and skimmers.

- On water:

If the product is spilled in a river or in the sewers, notify the authorities of the

possible presence of surface effluent.

Spill cleanup methods: If the material has been discharged into a stream or a sewer, inform the authorities

of the possible presence of surface effluent.



Product name: NEVASTANE SL 100 Page: 3/6

SDS n° :33841-44 Version :1.00 Version of :2004-11-30

This sheet supersedes the one dated :2004-06-21

7. HANDLING AND STORAGE

HANDLING:

Prevention of user exposure: Ventilate extensively if the formation of vapours, fumes, mists or aerosol is a risk.

Make all the necessary arrangements in order to reduce exposure risk, notably to

products in use or to wastes.

Keep away from combustible substances; keep away from food and beverages.

Prevention of fire and explosion: Empty containers may contain flammable or explosive vapours.

There is a fire hazard associated with rags, paper or any other material used to

remove spills which become soaked with product.

Avoid accumulation of these: they are to be disposed off safely after use.

Precautions: Avoid static electricity build up with connection to earth.

Set up machinery and equipment so as to avoid the risk of accidental spills or splashes onto hot machine parts and electrical contacts (on joint failure, for

example).

STORAGE:

Technical measures: Make the necessary arrangements to prevent water and soil pollution.

Storage precautions : - Suitable:

Store at room temperature, protected against contact with water and moisture, and

away from any source of ignition.

- To be avoided:

Do not store exposed to the elements.

Incompatible products : Dangerous reaction with strong oxidizing agents.

Packaging materials : - Recommended:

Use only hydrocarbon-resistant containers, joints, pipes, etc.

Keep in original container if possible.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Technical measures: Use the product in a properly ventilated atmosphere.

When working on enclosed place (tanks, reservoirs...), make sure that atmosphere is

not suffocating and/or wear recommended equipment.

Occupational exposure limit : $\qquad \qquad \text{. oil mist: } 10 \text{mg/m3, for 15 minutes}$

. oil mist : 5mg/m3, for $8\ hours$

Hand protection: Impermeable hydrocarbon-proof gloves.

recommended material: nitrile, neoprene.

The break through times of the same type of glove of different manufacturers can be very different - even if the layer thickness is similar. Therefore the break through times have to be found out from the manufacturer of the protective gloves

themselves.

The demands on the gloves are determined by the conditions in practice (e.g. multiple use, mechanical load, temperature, strength and duration of exposition). Before choosing suitable gloves, it is recommended that the user tests the gloves.

Eye protection : Goggles, in case of risk of splashing.

Skin and body (other than the hands) protection: As required, wear a face mask, hydrocarbon-proof clothing, and safety boots (when

handling drums).

Don't wear rings, watches or anything similar which can retain the product and may

give rise to skin conditions.



Product name: NEVASTANE SL 100 Page: 4/6

SDS n° :33841-44 Version :1.00 Version of :2004-11-30

This sheet supersedes the one dated :2004-06-21

Hygienic work practices: Avoid prolonged and repeated contact with the skin, especially with used or waste

product

If the product comes into contact with the skin, wash the affected area immediately

and copiously with soap and water. Do not use abrasives, solvents or fuels.

Do not put the product-soaked rags into the pockets of working clothes.

Do not eat, drink or smoke while handling the product. Do not use cloths stained with the product to dry hands. Immediately remove all soiled or stained clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Liquid

Colour: = < 1 (NF T 60-104)

Odour: Characteristic

Density/specific gravity: 843 - 859 kg/m3

Temperature (°C) 15

Flash point : > 200 ° C OC (Open cup).

Température d'auto-inflammation : > 250 ° C (ASTM E 659)

Solubility: - in water:

Insoluble and immiscible. - in organic solvents :

Soluble in many common solvents.

Partition coefficient (log Pow): Log Pow > 6

Temperature (°C) 20

Viscosity: 90 - 110 mm2/s

Temperature (°C) 40

10. STABILITY AND REACTIVITY

Stability: The product is stable at normal storage, handling and use temperatures.

Conditions to avoid: Heat (temperatures above flash point), sparks, ignition points, flames, static

electricity

Materials to avoid: Avoid contact with strong oxidizers

Hazardous decomp. products: Incomplete combustion and thermolysis produces potentially toxic gases such as

CO, CO2, various hydrocarbons, aldehydes and soot.

11. TOXICOLOGICAL INFORMATION

Acute toxicity / Local effect :

Inhalation, comments: Risk is improbable under normal conditions of use

Inhalation of high concentrations of vapour or aerosols may cause irritation of the

upper respiratory tract.

Skin contact, comments: Risk is improbable under normal conditions of use.

In case of ingestion of small quantities, no important effect observed. in case of

ingestion of larger amounts: abdominal pain, diarrhea, ...

CHRONIC TOXICITY OR LONG-TERM TOXICITY:

Skin contact: Characteristic skin affections (oil blisters) may develop following prolonged and

repeated exposure through contact with stained clothing



Safety Data Sheet NEVASTANE SL 100 Product name: Page: 5/6 SDS n°:33841-44 Version:1.00 Version of :2004-11-30 This sheet supersedes the one dated :2004-06-21 Sensitization: Contains a sensitising substance May cause sensitisation by skin contact 12. ECOLOGICAL INFORMATION Comments about ecotoxicity: Experimental data on the finished product are not available. It is considered to present a little danger for aquatic life. no information available for used product Mobility: - Air: there is a slow loss by evaporation. - Soil: Given its physical and chemical characteristics, the product generally shows little mobility in the ground. - Water: The product is insoluble; it spreads on the surface of the water 13. DISPOSAL CONSIDERATIONS Waste disposal: Dispose of in a safe manner, in accordance with local regulations. If need be, collection by an authorised waste contractor and regeneration or incineration at an approved installation. Waste class: The waste classification is dependant on the composition of the product at the time of disposal. The waste classification mentioned here represents only a recommendation. The waste producer is responsible for the correct specification of the waste. The specification of the waste classification should be in arrangement with the authorised waste disposal company. Disposal of contaminated packaging: Proceed in compliance with the prevailing regulations. 14. TRANSPORT INFORMATION UN N°: not applicable Road (ADR) / Rail (RID): Transport by barge (ADNR): Marine (IMO-IMDG): Air (ICAO/IATA): 15. REGULATORY INFORMATION Not applicable Risk phrases: None Safety phrases: None Other: - Contains:

> N-phenyl-1-naphthylamine May produce an allergic reaction



Product name: NEVASTANE SL 100 Page : 6/6

SDS n° :33841-44 Version :1.00 Version of :2004-11-30

This sheet supersedes the one dated :2004-06-21

EU directives: Hazardous preparations directive 1999/45/EC modified (Directive 2001/60/EC).

D. 67/548/EC modified by D. 2001/59/EC (28th APT)

This product fulfills the requirements of the European directives:

76/769/EEC 2000/53/EC 2002/95/EC 2002/96/EC 2003/11/EC

INVENTORIES:

CANADA (DSL): All components on DSL, NDSL

EUROPE (EINECS): One or more components not found on EINECS inventory

PHILIPPINES (PICCS): One or more components not found on PICCS

USA (TSCA): All components listed in TSCA

AUSTRALIAN (AICS): One or more components not found on AICS

KOREA (ECL): One or more components not found on ECL

16. OTHER INFORMATION

Explanations of R-phrases in section 2: R-36/38 Irritating to eyes and skin.

R-51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

R-22 Harmful if swallowed.

R-43 May cause sensitization by skin contact.

*Revision date: 2004-11-30 *Supersedes the data sheet of: 2004-06-21

* Information revised since the previous version of the SDS:

*SDS No.: LT-DS-5426 Safety Data Sheet status: Approved.

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.