

Product name: SERIOLA 2100 Page: 1/5

SDS n° :54140-44 Version :1.00 Version of :2005-02-28

This sheet supersedes the one dated :2004-06-22

PRODUCT LABELS

LABELLING (standard or EU):

R-phrases: Not classified.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY UNDERTAKING

Name of the product: SERIOLA 2100

Code No.: 794

Product application: Heat transfer fluid

Supplier: TOTAL UK LIMITED

40 Clarendon Road

Watford. Hertfordshire. WD17 1TQ

UNITED KINGDOM Tel: 01923 694000 Fax: 01923 694400

Contact: Specific Product Related Info: 01977 636200

Emergency telephones: UK -

01923 694000

Poisons Advice Centre: NHS Direct: 0845 46 47 / Textphone: 0845 606 46 47

Burns Units: NHS Direct: 0845 46 47 / Textphone: 0845 606 46 47

See local details at end of sheet:

Manufacturer: TOTAL UK LIMITED

40 Clarendon Road

Watford. Hertfordshire. WD17 1TQ

UNITED KINGDOM Tel: 01923 694000 Fax: 01923 694400

2. HAZARDS IDENTIFICATION

Health effects: Under normal conditions of use, the product holds no danger of intoxication

Environmental impact: Do not discharge this product into the environment.

Physico-chemical hazards: No specific risk of fire or explosion under normal conditions of use

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature: Petroleum-derived severely refined mineral-base product

Content in PAH according to IP 346 method < 3%

Composition comments: Substances contributing to hazards:

None, to our knowledge

4. FIRST AID MEASURES

IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.

Inhalation: Inhalation of heavy concentrations of vapour, fumes or spray, may cause mild

irritation of the throat.

Transport the person into fresh air, keep warm and allow to rest.



Product name: SERIOLA 2100 Page: 2/5

SDS n°:54140-44 Version :1.00 Version of :2005-02-28

This sheet supersedes the one dated :2004-06-22

Ingestion: Possible risk of vomiting and diarrhoea.

Do not induce vomiting to avoid the risk of aspiration into the respiratory tract.

Give nothing to drink

Skin contact: Immediately remove all soiled or stained clothing.

Wash the affected area immediately and repeatedly with soap and water.

If the skin is exposed to high-pressure spray, the product may enter the human body. In all such cases the affected person must be taken to hospital, even if no sign of

injury can be detected.

Eye contact: Keep eyes open and rinse immediately and repeatedly with water for at least 15

minutes.

Aspiration: If the product is believed to have entered the lungs (in case of vomiting, for

example), take the person to hospital for immediate care.

5. FIRE FIGHTING MEASURES

Extinguishing media: - suitable:

Foam, carbon dioxide (CO2), powder.

- not recommended:

do not use water jets (stick jets) for extinguishing fire since they could help to

spread the flames.

Specific hazards: Incomplete combustion and thermolysis produce gases of varying toxicity such as

CO, CO2, various hydrocarbons, aldehydes and soot. These may be highly

dangerous if inhaled.

Protective measures for firefighters: Insulated breathing apparatus must be worn in confined premises with heavy

concentrations of fumes and gases.

6. ACCIDENTAL RELEASE MEASURES

Personal protection:

As applicable in view of the risk of spills and splashes, wear suitable protective

clothing, gloves and goggles.

After spillage / leakage : - On the soil:

Surfaces on which the product has been spilled may become slippery. Do not allow the product to enter sewers or rivers or contaminate the soil.

Recover with mechanical means such as pumps and skimmers.

- On water:

Floating absorbant material, then mechanical recovery.

If the product is spilled in a river or in the sewers, notify the authorities of the

possible presence of surface effluent.

Spill cleanup methods : - Recovery:

Use mechanical means such as pumps, skimmers and absorbent materials.

- Elimination:

Hand over contaminated materials to an approved collector - see also section 13.

7. HANDLING AND STORAGE

HANDLING:

Prevention of user exposure: Ventilate extensively if the formation of vapours, fumes, mists or aerosol is a risk.

Make all the necessary arrangements in order to reduce exposure risk, notably to

products in use or to wastes.

Keep away from combustible substances; keep away from food and beverages.

Prevention of fire and explosion: Empty containers may contain flammable or explosive vapours.

There is a fire hazard associated with rags, paper or any other material used to

remove spills which become soaked with product.

Avoid accumulation of these: they are to be disposed off safely after use.



Safety Data Sheet SERIOLA 2100 Product name: Page: 3/5 SDS n°:54140-44 Version:1.00 Version of :2005-02-28 This sheet supersedes the one dated :2004-06-22 Avoid static electricity build up with connection to earth. Precautions: Set up machinery and equipment so as to avoid the risk of accidental spills or splashes onto hot machine parts and electrical contacts (on joint failure, for example). STORAGE: Technical measures: Make the necessary arrangements to prevent water and soil pollution. Storage precautions: - Suitable: Store at room temperature, protected against contact with water and moisture, and away from any source of ignition. Keep containers closed when not in use - To be avoided: Do not store exposed to the elements. Incompatible products: Dangerous reaction with strong oxidizing agents. Packaging materials: - Recommended: Use only hydrocarbon-resistant containers, joints, pipes, etc. Keep in original container if possible. 8. EXPOSURE CONTROLS/PERSONAL PROTECTION Technical measures: Use the product in a properly ventilated atmosphere. When working on enclosed place (tanks, reservoirs...), make sure that atmosphere is not suffocating and/or wear recommended equipment. Occupational exposure limit: . oil mist: 10mg/m3, for 15 minutes . oil mist: 5mg/m3, for 8 hours Hand protection: Impermeable hydrocarbon-proof gloves. recommended material: nitrile, neoprene. The break through times of the same type of glove of different manufacturers can be very different - even if the layer thickness is similar. Therefore the break through times have to be found out from the manufacturer of the protective gloves themselves. The demands on the gloves are determined by the conditions in practice (e.g. multiple use, mechanical load, temperature, strength and duration of exposition). Before choosing suitable gloves, it is recommended that the user tests the gloves. Eye protection: Goggles, in case of risk of splashing. Skin and body (other than the hands) protection: As required, wear a face mask, hydrocarbon-proof clothing, and safety boots (when handling drums). Don't wear rings, watches or anything similar which can retain the product and may give rise to skin conditions. Hygienic work practices: Avoid prolonged and repeated contact with the skin, especially with used or waste Immediately remove all soiled or stained clothing. If the product comes into contact with the skin, wash the affected area immediately and copiously with soap and water. Do not use abrasives, solvents or fuels. Do not use cloths stained with the product to dry hands. Do not put the product-soaked rags into the pockets of working clothes. Do not eat, drink or smoke while handling the product. 9. PHYSICAL AND CHEMICAL PROPERTIES Appearance: Liquid

Colour: Yellow to brown

Odour: Characteristic.



Product name: SERIOLA 2100 Page: 4/5

SDS n°:54140-44 Version :1.00 Version of :2005-02-28

This sheet supersedes the one dated :2004-06-22

Density/specific gravity: 889 kg/m3

Temperature (°C) 15

Flash point : $210 \,^{\circ}$ C (ASTM D 93)

Température d'auto-inflammation : 250 ° C (ASTM E 659)

Comments on autoignition temperature: This temperature may be significantly lower under particular conditions (slow

oxidation on finely divided materials...).

Partition coefficient (log Pow): Log Pow (Mineral oil) > 6

Viscosity: 6.2 mm2/s

Temperature (°C) 100

10. STABILITY AND REACTIVITY

Stability: The product is stable at normal storage, handling and use temperatures.

Conditions to avoid: Heat (temperatures above flash point), sparks, ignition points, flames, static

electricity

Materials to avoid: Avoid contact with strong oxidizers

Hazardous decomp. products: Incomplete combustion and thermolysis produces potentially toxic gases such as

CO, CO2, various hydrocarbons, aldehydes and soot.

11. TOXICOLOGICAL INFORMATION

Acute toxicity / Local effect:

Inhalation, comments: - Inhalation :

Risk is improbable under normal conditions of use

Inhalation of high concentrations of vapour or aerosols may cause irritation of the

upper respiratory tract.

Skin contact, comments: - Contact with skin:

Risk is improbable under normal conditions of use.

Ingestion, comments: - Ingestion :

In case of ingestion of small quantities, no important effect observed. in case of

ingestion of larger amounts: abdominal pain, diarrhea, ...

CHRONIC TOXICITY OR LONG-TERM TOXICITY:

Skin contact: Characteristic skin affections (oil blisters) may develop following prolonged and

repeated exposure through contact with stained clothing

Sensitization: To our knowledge, the product does not cause aggravated sensitivity.

12. ECOLOGICAL INFORMATION

Comments about ecotoxicity: Experimental data on the finished product are not available.

It is considered to present a little danger for aquatic life.

no information available for used product

Mobility: - Air:

there is a slow loss by evaporation.

- Soil:

Given its physical and chemical characteristics, the product generally shows little

mobility in the ground.

- Water:

The product is insoluble; it spreads on the surface of the water



Product name: SERIOLA 2100 Page: 5/5

SDS n°:54140-44 Version :1.00 Version of :2005-02-28

This sheet supersedes the one dated :2004-06-22

Persistence and degradability: No experimental information about the finished product.

The product should offer slow biodegradability

13. DISPOSAL CONSIDERATIONS

Waste disposal: Dispose of in a safe manner, in accordance with local regulations.

If need be, collection by an authorised waste contractor and regeneration or

incineration at an approved installation.

Waste class: The waste classification is dependant on the composition of the product at the time

of disposal.

The waste classification mentioned here represents only a recommendation. The waste producer is responsible for the correct specification of the waste. The specification of the waste classification should be in arrangement with the

authorised waste disposal company.

Disposal of contaminated packaging: Proceed in compliance with the prevailing regulations.

14. TRANSPORT INFORMATION

UN N°: not applicable

Road (ADR) / Rail (RID):

Class: Not restricted for transport.

Transport by barge (ADNR):

Marine (IMO-IMDG):

Air (ICAO/IATA):

15. REGULATORY INFORMATION

Risk phrases: Not classified.

16. OTHER INFORMATION

HSE Infoline: 08701 545500 / Minicom: 02920 808537

This sheet is in compliance with the standards defined by the directives 91/155/CEE, 93/112/CEE, 2001/58/CE and the article 14 of the

directive 1999/45/EC.

Revision date: 2005-02-28 Supersedes the data sheet of: 2004-06-22

* Information revised since the previous version of the SDS :

SDS No.: LT-DS-1569
Safety Data Sheet status: Approved.

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.