



NEPTUNA 2T SUPER SPORT

TC-W3[®]



Mineral lubricant for 2 strokes gasoline engines of leisure craft.

SPECIFICATIONS AND APPROVALS

International specifications NMMA TC-W3[®] RL-00198F

Meets the requirements of
JOHNSON, MARINER, MERCURY, SUZUKI, YAMAHA...

APPLICATIONS

TOTAL NEPTUNA 2T SUPER SPORT is a **mineral** lubricant adapted to **2 strokes gasoline engines**.

The mixing with the fuel should be in accordance with the manufacturer's recommendations.

PERFORMANCES AND CUSTOMER BENEFITS

TOTAL NEPTUNA SUPER SPORT exhibits excellent lubrication guaranteeing **reduced wear**.

Outstanding detergent property helps prevent the clogging of piston ports avoids spark plug fouling and extends engine lifespan.

Its **anti-rust** and **anti-corrosion properties** protect engines during prolonged stop.

PHYSICAL AND CHEMICAL CHARACTERISTICS*

TOTAL NEPTUNA 2T SUPER SPORT		Method	Value
Density at 15°C	kg/m ³	ASTM D1298	867
Kinematic Viscosity at 40°C	mm ² /s	ASTM D445	50
Kinematic Viscosity at 100°C	mm ² /s	ASTM D445	8.5
Viscosity Index	-	ASTM D2270	146
Pour point	°C	ASTM D97	-36
Color	-	-	Blue-green

* The features mentioned above are average values obtained with some variability in production and do not constitute a specification.

TOTAL LUBRIFIANTS
562, avenue du Parc de l'Île
92029 Nanterre cedex
FRANCE

TOTAL NEPTUNA 2T SUPER SPORT
Update 07/2014
www.lubricants.total.com



This lubricant does not cause adverse health effects when used in the intended application.
A safety datasheet is accessible on request from your local dealer or on the website www.quickfds.com