

RUBIA S

20W-20



Monograde lubricant for Diesel engines

UTILISATION

- Recommended for hydraulic systems when the manufacturer requires an engine oil with an appropriate grade for these applications.

PERFORMANCES

Specifications

ACEA E2
API CF/SF

OEMs approvals

MERCEDES MB-Approval 228.0
MAN 270
MIL-L 2104 E

CUSTOMER BENEFITS

Technical performances

- Monograde
- High viscosity index
- High stability in operation
- Exceptional detergency level
- Very high dispersancy level
- Excellent antiwear and anticorrosion properties
- Excellent antioxydant, antirust and antifoaming properties

CHARACTERISTICS

	Units	SAE Grade 20W20
Volumetric mass at 15°C	kg/m ³	885
Viscosity at 100°C	mm ² /s	9
Viscosity index	-	98
Flash point	°C	>200
Pour point	°C	-30
T.B.N	mgKOH/g	11.2

The typical characteristics mentioned represent mean values.

TOTAL LUBRIFIANTS
562 avenue du Parc de L'Île
92029 NANTERRE Cedex
France

RUBIA S 20W20
October 2011
N° MPR 10/11



This lubricant, when used according to our recommendations and for the purpose for which it is intended, presents no particular hazards. A safety data sheet complying with current EC legislation can be obtained from your local commercial adviser.