



# TRANSELF BLS 90



Lubrication of limited slip differentials of self-locking axles.

## USES

**Axles in cars, trucks, construction and agricultural machinery**

- Lubrication of limited slip differentials of self-locking axles fitted in passenger cars, utility vehicles, earth moving and agricultural equipment.

## PERFORMANCES

**API GL-5**

**ZF APPROVED**

- Meets the requirements of the international API specifications.
- Manufacturer approval :
  - ZF TE-ML 05C, 12C
- Meets the requirements :
  - FORD M2C 104A
  - STEYR

## CLIENTS BENEFITS

**Protection of the axle devices**

**Driving comfort**

- Extreme pressure.
- Stable at high temperatures.
- Anti-rust and anti-corrosion properties.
- Provides excellent protection against worm or stripped gear teeth under all operating conditions,
- Eliminates vibration and chatter in stressed self-locking axles.

## CHARACTERISTICS

	Unit	Grade 90
Density at 15 °C	---	0.899
Kinematic viscosity at 40°C	mm <sup>2</sup> /s	166
Kinematic viscosity at 100 °C	mm <sup>2</sup> /s	17
Viscosity index	---	109
Pour point	°C	- 33

The values in this table are typical values given as an indication

TOTAL LUBRIFIANTS  
La Spazio Box C40  
562 Av du Parc de l'île, 92029 Nanterre Cedex  
1/1

TRANSELF BLS 90  
August 2010  
N° MPR/07/05



This lubricant, when used in accordance with our recommendations and for the application for which it is intended, does not constitute a special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant