

FINOL PERFORMANCE E3 15W40

APPLICATIONS

Finol Performance E3 15W40 is a mineral lubricant for on road diesel applications.

It is recommended for previous Euro 3 engine generations.

SPECIFICATIONS

- ACEA E2
- API CG-4 /SJ
- MERCEDES BENZ 228.3/ 229.1
- Man 3275
- Mack EO-L
- Volvo VDS 3

ADVANTAGES

- **Finol Performance E3 15W-40 retains excellent viscosity stability in service ensuring efficient engine lubrication in severe conditions.**
- **Detergent, dispersant and anti -wear properties keep the engine clean and enable efficient control of soot, sludge and piston deposits.**
- **Detergent, antioxidant and anti-corrosion additives help reach standard oil drain intervals.**

TYPICAL CHARACTERISTICS

TEST	UNITS	Method	Value
Sulphated ash	% m/m	ASTM D 874	1.2
Kinematic Viscosity at 40°C	mm ² /s	ASTM D 445	101
Kinematic Viscosity at 100°C	mm ² /s	ASTM 445	14
Viscosity Index	-	ASTM D2270	141
Flash point	°C		226
Pour point	°C	NF T 60 105	-33
TBN	mgKOH/g	ASTM D2896	8.5

The features mentioned above are average values obtained with some variability in production and do not constitute a specification

Before using the product, it is important to check the service manual of the vehicle: the drain is carried out according to the manufacturer's requirements

The product should not be stored at a temperature above 60 °C. Exposure to strong sunlight, extreme cold or high temperature variations must be avoided.

All packages should be protected from bad weather conditions. The drums should be stored horizontally to avoid a possible contamination by water and the damage of the product label.

FINOL PERFORMANCE E 3 15W40

SHEET UPDATED 18/09/2018