

FINOL COOLANT SI-OAT R.T.U

APPLICATIONS

READY TO USE VERY LONG-LIFE SI-OAT COOLANT/ANTIFREEZE

SPECIFICATIONS

- AFNOR NFR 15-601 BS 6580:2010 SAE J 1034
 - ASTM D 3306 ASTM 4985 CUNA NC 956-16
- Meets the requirements level of the following manufacturers.
- VW/AUDI/ SEAT/ SKODA /DAIMLER /MERCEDES BENZ.
 - LAMBORGHINI / BENTLEY / PORSCHE / BUGATTI /VW TL 774G
 - MAN 324 TYPE SI-OAT / CUMMINS CES 14603 / SCANIA TB -1451

ADVANTAGES

- Finol Coolant SI-OAT is a very long-life coolant.
- Finol Coolant SI-OAT has fast effective protective properties, it provides a high level of protection against damage cause by freezing, cavitation, corrosion and overheating.
- Finol Coolant SI-OAT is recommended for both light and heavy-duty vehicles
- Mercedes Benz, Man, Scania, Cummins, Euro 6 engines.

TYPICAL CHARACTERISTICS

TEST	UNIT	METHOD	RESULT
APPERANCE			CLEAR LIQUID
COLOUR			PINK
DENSITY AT 20°C	KG/L	ASTM D 1122	1.075
REFRACTIVE INDEX AT 20°C		ASTMD 1218	1.3871
AQ	mLHCl.1N	ASTM D 1121	9.9
PH AT 20°C		ASTM D 1287	8.3
FREEZING POINT	°C	ASTM D 1177	.38

Sheet updated 03/12/2018

Finol Oils Unlimited Company Trading as Finol Oils

3 Stannaway Drive, Crumlin, Dublin 12, D12 X2PN

Tel: +353 1 455 5484 | Fax: +353 1 455 5610 | Email: finol@inol.ie | www.finol.ie

Registered in Ireland No. 58570