

FINOL CHALLENGE PRO-V-0W20

APPLICATIONS

Finol Challenge Pro V 0W-20 is a premium, synthetic technology engine oil that lowers friction and provides excellent protection against wear, rust and deposits.

It is particularly suitable for use in VOLVO Drive-E engines, where the manufacturer recommends the usage of the oil approved to VOLVO VCC RBS0-2AE and SAE 0W-20 Grade

Finol Challenge Pro V 0W-20 offers outstanding fuel economy properties while maximizing engine performance in the long run.

SPECIFICATIONS

- ACEA A1 /B1
- VOLVO- RBS0-2AE 0W20
- Petrol & Diesel Engines
- Fuel Economy

ADVANTAGES

- Excellent Engine Performance
- Engine protection and cleanliness
- Reducing environmental impact: 3.44% reduction in fuel consumption
- Easier cold starting performance

TYPICAL CHARACTERISTICS

TEST	UNIT	Test Method	Result
Viscosity Grade		SAE J 300	0W20
Density at 15°C	Kg/m ³	ASTM D 1298	0.858
Kinematic viscosity at 40°C	mm ² /s	ASTM D 445	48.60
Kinematic viscosity at 100°C	mm ² /s	ASTM D 455	9.20
Viscosity index	-	ATSM D 2270	174
OC Flash Point	°C	ASTM D 92	196

The features mentioned above are obtained with the usual tolerance in production and do not constitute a specification.

The product should not be stored at a temperature above 60 °C. Exposure to strong sunlight, extreme cold or high temperature variations must be avoided.

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.

A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or down loaded from www.finol.ie

SHEET UPDATED 17/10/2018