

# FINOL CHALLENGE PRO E 0W30

## APPLICATIONS

FINOL CHALLENGE PRO E 0W30 is a synthetic technology engine oil that has been developed to cover the most stringent requirements of both petrol and diesel engines.

This engine oil can be used in the most difficult operating conditions (motorways city driving), and is appropriate for all driving types and all seasons.

## SPECIFICATIONS

FINOL CHALLENGE PRO E 0W30, meets the following specifications.

- ACEA A3/B4
- API SL/CF
- BMW LL-01
- MB 229.5
- VW 502/505
- VOLVO VCC 95200356

## ADVANTAGES

- **Engine protection, cleanliness and performance:** This oil contains detergent and dispersive additives that keep the engine clean and thus preserve its power
- **Easier cold starts:** FINOL CHALLENGE PRO E 0W-30 is perfectly adapted for cold starting in extreme weather conditions and ensures a good protection of mechanical parts at high temperatures.
- **Fuel Savings:** Thanks to its exceptional fluidity, this oil reduces friction and therefore creates significant fuel savings and reduces CO2 emissions
- **Anti-wear protection:** this oil ensures optimum engine longevity with its anti-wear properties that protect the engine's most sensitive parts
- **Oxidation resistance:** this lubricant allows extra long drain intervals.

**TYPICAL CHARACTERISTICS**

TEST	UNITS	Method	Value
Kinematic Viscosity at 40°C	mm <sup>2</sup> /s	ASTM D 445	68.7
Kinematic Viscosity at 100°C	mm <sup>2</sup> /s	ASTM 445	12.3
Viscosity Index	-	ASTM D2270	170
Flash point	°C	NF EN ISO 2592	226
Pour point	°C	NF T 60 105	-45
TBN	mgKOH/g	ASTM D2896	8.8

The features mentioned above are average values obtained with some variability in production and do not constitute a specification

Before using the product, it is important to check the service manual of the vehicle: the drain is carried out according to the manufacturer's requirements

The product should not be stored at a temperature above 60 °C. Exposure to strong sunlight, extreme cold or high temperature variations must be avoided.

All packages should be protected from bad weather conditions. The drums should be stored horizontally to avoid a possible contamination by water and the damage of the product label.

**FINOL CHALLENGE PRO E 0W30**

Sheet updated 10/09/2018