

# FINOL PERFORMANCE S 30

## APPLICATIONS

Finol Performance S 30 is a monograde lubricant, suitable for hydraulic circuits, petrol, diesel engines & gearboxes in trucks, agricultural equipment, lawnmowers, earthmoving & quarry machinery

## SPECIFICATIONS

- API CF/SF
- Caterpillar TO-2

## ADVANTAGES

Performance S30 Detergent, dispersant and anti-wear properties keep the engine clean and enable effective control of soot, sludge and piston deposits.

Performance S30 exhibits good resistance to oxidation, avoiding oil ticking and preventing the formation of deposits and varnish.

## TYPICAL CHARACTERISTICS

TEST	UNITS	Method	Value
Viscosity grade			SAE 30
Density at 15°C	Kg/m <sup>3</sup>	ASTM D 1298	895
Kinematic Viscosity at 40°C	mm <sup>2</sup> /s	ASTM D 445	103
Kinematic Viscosity at 100°C	mm <sup>2</sup> /s	ASTM D 445	11.5
Viscosity Index	-	ASTM D 2270	98
Flash point	°C	ASTM D 92	220
Pour point	°C	ASTM D 97	-24
TBN	mgKOH/g	ASTM D 2896	11
Sulphated Ash	%m/m	ASTM D 874	1.52

The features mentioned above are average values obtained with some variability in production and do not constitute a specification

Before using the product, it is important to check the service manual of the vehicle: the drain is carried out according to the manufacturer's requirements

The product should not be stored at a temperature above 60 °C. Exposure to strong sunlight, extreme cold or high temperature variations must be avoided.

All packages should be protected from bad weather conditions. The drums should be stored horizontally to avoid a possible contamination by water and the damage of the product label.

Sheet updated 27/09/2018