

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## PURITY<sup>TM/MC</sup> FG SILICONE SPRAY

000003000275



Version 3.4

Revision Date 2022/08/16

Print Date 2022/08/16

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Product name : PURITY<sup>TM/MC</sup> FG SILICONE SPRAY

Product code : PFSI, PFSIB12

Unique Formula Identifier (UFI) : 7Y71-DNPM-R80H-SX75

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Aerosol spray lubricant.  
NSF H1 Registered.

All components comply with FDA 21 CFR 178.3570 "Lubricants with Incidental Food Contact". It is intended for application on industrial and food equipment. It should not be added directly to the food product.

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer or supplier's details

HollyFrontier LSP Europe BV  
Mainhavenweg 6  
1043 AL Amsterdam  
The Netherlands

Telephone : +31 (0)85 4000080

E-mail address of person responsible for the SDS : EUSDS@hfsinclair.com

#### 1.4 Emergency telephone number

Emergency telephone number : CHEMTREC: +1-703-741-5970;  
Poison Control Centre: Consult local telephone directory for emergency number(s).  
Please refer to Section 15 for the European Poison Center Phone Numbers.

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.  
H229: Pressurised container: May burst if heated.

Skin irritation, Category 2 H315: Causes skin irritation.

Specific target organ toxicity - single ex- H336: May cause drowsiness or dizziness.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## PURITY<sup>TM/MC</sup> FG SILICONE SPRAY

000003000275



Version 3.4

Revision Date 2022/08/16

Print Date 2022/08/16

posure, Category 3, Central nervous system

Aspiration hazard, Category 1

H304: May be fatal if swallowed and enters airways.

Short-term (acute) aquatic hazard, Category 1

H400: Very toxic to aquatic life.

Long-term (chronic) aquatic hazard, Category 1

H410: Very toxic to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

:



Signal word

:

Danger

Hazard statements

:

H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

:

#### Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P273 Avoid release to the environment.

#### Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
P331 Do NOT induce vomiting.  
P391 Collect spillage.

#### Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

#### Hazardous components which must be listed on the label:

Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha  
n-heptane  
3-methylhexane  
methylcyclohexane

### 2.3 Other hazards

None known.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## PURITY<sup>TM/MC</sup> FG SILICONE SPRAY

000003000275



Version 3.4

Revision Date 2022/08/16

Print Date 2022/08/16

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha	64742-49-0  265-151-9 649-328-00-1	Asp. Tox. 1; H304	20 - 30
n-heptane	142-82-5  205-563-8 601-008-00-2	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin irr. 2; H315 STOT SE 3; H336 (Central nervous system) Aquatic Acute 1; H400 Aquatic Chronic 1; H410	7 - 13
3-methylhexane	589-34-4  209-643-3 601-008-00-2	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin irr. 2; H315 STOT SE 3; H336 (Central nervous system) Aquatic Acute 1; H400 Aquatic Chronic 1; H410	5 - 10
methylcyclohexane	108-87-2  203-624-3 601-018-00-7	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin irr. 2; H315 STOT SE 3; H336 (Central nervous system) Aquatic Chronic 2; H411	3 - 7
2-methylhexane	591-76-4  209-730-6 601-008-00-2	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin irr. 2; H315 STOT SE 3; H336 (Central nervous system) Aquatic Acute 1; H400 Aquatic Chronic 1; H410	3 - 5
2,3-dimethylpentane	565-59-3  209-280-0 601-008-00-2	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin irr. 2; H315 STOT SE 3; H336	1 - 3

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## PURITY<sup>TM/MC</sup> FG SILICONE SPRAY

000003000275



Version 3.4

Revision Date 2022/08/16

Print Date 2022/08/16

		(Central nervous system) Aquatic Acute 1; H400 Aquatic Chronic 1; H410	
3-ethylpentane	617-78-7  210-529-0 601-008-00-2	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin irr. 2; H315 STOT SE 3; H336 (Central nervous system) Aquatic Acute 1; H400 Aquatic Chronic 1; H410	1 - 3
3,3-dimethylpentane	562-49-2  209-230-8 601-008-00-2	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin irr. 2; H315 STOT SE 3; H336 (Central nervous system) Aquatic Acute 1; H400 Aquatic Chronic 1; H410	0.1 - 0.5

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- If inhaled : Move to fresh air.  
Artificial respiration and/or oxygen may be necessary.  
Seek medical advice.
- In case of skin contact : In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Wash skin thoroughly with soap and water or use recognized skin cleanser.  
Wash clothing before reuse.  
Seek medical advice.
- In case of eye contact : Remove contact lenses.  
Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Obtain medical attention.
- If swallowed : Rinse mouth with water.  
DO NOT induce vomiting unless directed to do so by a physician or poison control center.  
Never give anything by mouth to an unconscious person.  
Seek medical advice.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## PURITY<sup>TM/MC</sup> FG SILICONE SPRAY

000003000275



Version 3.4

Revision Date 2022/08/16

Print Date 2022/08/16

### 4.2 Most important symptoms and effects, both acute and delayed

Risks : First aider needs to protect himself.

### 4.3 Indication of any immediate medical attention and special treatment needed

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Dry chemical  
Carbon dioxide (CO<sub>2</sub>)  
Water spray  
Alcohol-resistant foam  
Water fog

Unsuitable extinguishing media : Do NOT use water jet.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : If the product release cannot be shut off safely, allow the product to burn itself out.  
Cool closed containers exposed to fire with water spray.

Hazardous combustion products : Carbon oxides (CO, CO<sub>2</sub>), smoke and irritating vapours as products of incomplete combustion.

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus and full protective wear. Wear a positive-pressure supplied-air respirator with full facepiece.

Further information : Prevent fire extinguishing water from contaminating surface water or the ground water system.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Ensure adequate ventilation.  
Evacuate personnel to safe areas.  
Remove all sources of ignition.  
Mark the contaminated area with signs and prevent access to unauthorized personnel.  
Only qualified personnel equipped with suitable protective equipment may intervene.

### 6.2 Environmental precautions

Environmental precautions : If the product contaminates rivers and lakes or drains inform respective authorities.  
Do not allow uncontrolled discharge of product into the environment.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## PURITY<sup>TM/MC</sup> FG SILICONE SPRAY

000003000275



Version 3.4

Revision Date 2022/08/16

Print Date 2022/08/16

### 6.3 Methods and material for containment and cleaning up

- Methods for cleaning up : Prevent further leakage or spillage if safe to do so.  
Remove all sources of ignition.  
Non-sparking tools should be used.  
Use explosion-proof ventilation equipment.  
Soak up with inert absorbent material.  
Ensure adequate ventilation.  
Contact the proper local authorities.

### 6.4 Reference to other sections

For personal protection see section 8.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- Advice on safe handling : For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Do not ingest.  
Avoid contact with skin, eyes and clothing.  
Use only with adequate ventilation.  
Do not breathe vapours or spray mist.  
Keep away from heat and sources of ignition.  
Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity.
- Advice on protection against fire and explosion : Keep away from heat and sources of ignition.
- Hygiene measures : Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash face, hands and any exposed skin thoroughly after handling.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a dry, cool and well-ventilated place. Keep in properly labelled containers. Take measures to prevent the build up of electrostatic charge.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## PURITY<sup>TM/MC</sup> FG SILICONE SPRAY

000003000275



Version 3.4

Revision Date 2022/08/16

Print Date 2022/08/16

### 7.3 Specific end use(s)

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

### 8.2 Exposure controls

#### Engineering measures

Adequate ventilation to ensure that Occupational Exposure Limits are not exceeded.  
Use explosion-proof ventilation equipment.

#### Personal protective equipment

Eye protection : Wear face-shield and protective suit for abnormal processing problems.

Hand protection  
Material : neoprene, nitrile. Consult your PPE provider for breakthrough times and the specific glove that is best for you based on your use patterns. It should be realized that eventually any material regardless of their imperviousness, will get permeated by chemicals. Therefore, protective gloves should be regularly checked for wear and tear. At the first signs of hardening and cracks, they should be changed.

Remarks : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Filter type : organic vapour filter

Protective measures : Wash contaminated clothing before re-use.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state : Aerosol containing a liquefied gas

Colour : Clear, water-white

Odour : Mild Petroleum/Solvent

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## PURITY<sup>TM/MC</sup> FG SILICONE SPRAY



000003000275

Version 3.4

Revision Date 2022/08/16

Print Date 2022/08/16

Odour Threshold	:	No data available
Pour point	:	No data available
Initial boiling point and boiling range	:	estimated 48 °C
Flash point	:	-17.8 °C
		Method: Tag closed cup
Fire Point	:	No data available
Auto-Ignition Temperature	:	estimated 254 °C
Evaporation rate	:	No data available
Upper explosion limit / Upper flammability limit	:	estimated 9.5 %(V)
Lower explosion limit / Lower flammability limit	:	estimated 1.8 %(V)
Vapour pressure	:	estimated 3,083.3 hPa
Relative vapour density	:	No data available
Relative density	:	estimated 0.81
Density	:	No data available
Solubility(ies)		
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	No data available
Viscosity		
Viscosity, kinematic	:	No data available
Flammability	:	Extremely flammable aerosol. Extremely flammable in presence of open flames, sparks, and heat. Vapours are heavier than air and may travel considerable distance to sources of ignition and flash back.
Explosive properties	:	Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Container explosion may occur under fire conditions or when heated. Ruptured cylinders may rocket.

### 9.2 Other information

No data available



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## PURITY<sup>TM/MC</sup> FG SILICONE SPRAY

000003000275



Version 3.4

Revision Date 2022/08/16

Print Date 2022/08/16

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

#### 10.2 Chemical stability

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Hazardous polymerisation does not occur. Stable under normal conditions.

#### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

#### 10.5 Incompatible materials

Materials to avoid : Reactive with oxidising agents.

#### 10.6 Hazardous decomposition products

Hazardous decomposition products : May release CO<sub>x</sub>, smoke and irritating vapours when heated to decomposition.

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Eye contact  
Inhalation  
Skin contact

#### Acute toxicity

##### Product:

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

##### Components:

##### n-heptane:

Acute oral toxicity : LD50 (Rat): 25,000 mg/kg,

Acute inhalation toxicity : LC50 (Rat): > 73.5 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 3,000 mg/kg,

##### 3-methylhexane:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg,

Acute inhalation toxicity : LC50 (Rat): > 20 mg/l  
Exposure time: 4 h

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## PURITY<sup>TM/MC</sup> FG SILICONE SPRAY

000003000275



Version 3.4

Revision Date 2022/08/16

Print Date 2022/08/16

Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg,

### **methylcyclohexane:**

Acute oral toxicity : LD50 (Rat): > 4,000 mg/kg,

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg,

### **Skin corrosion/irritation**

#### **Product:**

Remarks : No data available

### **Serious eye damage/eye irritation**

#### **Product:**

Remarks : No data available

### **Respiratory or skin sensitisation**

No data available

### **Germ cell mutagenicity**

No data available

### **Carcinogenicity**

No data available

### **Reproductive toxicity**

No data available

### **STOT - single exposure**

No data available

### **STOT - repeated exposure**

No data available

### **Aspiration toxicity**

#### **Product:**

May be fatal if swallowed and enters airways.

---

## **SECTION 12: Ecological information**

### **12.1 Toxicity**

#### **Product:**

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## PURITY<sup>TM/MC</sup> FG SILICONE SPRAY

000003000275



Version 3.4

Revision Date 2022/08/16

Print Date 2022/08/16

Toxicity to algae/aquatic plants : Remarks: No data available

Toxicity to microorganisms :  
Remarks: No data available

### 12.2 Persistence and degradability

#### Product:

Biodegradability : Remarks: No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

Not relevant

### 12.6 Endocrine disrupting properties

No data available

### 12.7 Other adverse effects

No data available

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.  
Offer surplus and non-recyclable solutions to a licensed disposal company.  
Waste must be classified and labelled prior to recycling or disposal.  
Send to a licensed waste management company.  
Dispose of as hazardous waste in compliance with local and national regulations.  
Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.

---

## SECTION 14: Transport information

### International Regulations

#### IATA-DGR

UN/ID No. : UN 1950  
Proper shipping name : Aerosols, flammable  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : Flammable Gas  
Packing instruction (cargo) : 203

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## PURITY<sup>TM/MC</sup> FG SILICONE SPRAY



000003000275

Version 3.4

Revision Date 2022/08/16

Print Date 2022/08/16

aircraft)

### IMDG-Code

UN number : UN 1950  
Proper shipping name : AEROSOLS LIMITED QUANTITY

Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U  
Marine pollutant : no

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

Remarks : ADR: UN1950, AEROSOLS, 2.1  
ADN: UN1950, AEROSOLS, 2.1  
RID: UN1950, AEROSOLS, 2.1

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Water hazard class (Germany) : WGK 3 highly hazardous to water

### The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

IECSC : On the inventory, or in compliance with the inventory

### European Poison Center Phone Numbers

: Belgium - 070 245 245  
: Czech Republic - +420 224 919 293  
: Estonia - 16662  
: France - + 33 (0) 1 45 42 59 59  
: Ireland - 01 809 2166  
: Italy -  
Rome: 06 68593726  
Foggia: 800183459  
Naples: 081-5453333  
Rome: 06-49978000  
Rome: 06-3054343

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## PURITY<sup>TM/MC</sup> FG SILICONE SPRAY

000003000275



Version 3.4

Revision Date 2022/08/16

Print Date 2022/08/16

Florence: 055-7947819

Pavia: 0382-24444

Milan: 02-66101029

Bergamo: 800883300

Verona: 800011858

: Latvia - +371 67042473

: Lithuania - +370 687 533 78

: Netherlands - +31 (0)88 755 8000 (Only for the purpose of informing medical personnel in case of acute intoxications.)

: Poland - +48 71 343 30 08

: Spain - + 34 91 562 04 20

### 15.2 Chemical safety assessment

#### SECTION 16: Other information

##### Full text of H-Statements

H225	: Highly flammable liquid and vapour.
H304	: May be fatal if swallowed and enters airways.
H315	: Causes skin irritation.
H336	: May cause drowsiness or dizziness.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.

##### Full text of other abbreviations

Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Flam. Liq.	: Flammable liquids
Skin irr.	: Skin corrosion/irritation
STOT SE	: Specific target organ toxicity - single exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization;

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## PURITY<sup>TM/MC</sup> FG SILICONE SPRAY

000003000275



Version 3.4

Revision Date 2022/08/16

Print Date 2022/08/16

KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

For Copy of SDS

: Internet: [lubricants.petro-canada.com/sds](http://lubricants.petro-canada.com/sds)  
Europe, telephone: 00-800-7387-6000  
For Product Safety Information: 1 905-491-0565

Prepared by

: Product Safety: +1 905-491-0565

### Classification of the mixture:

Aerosol 1	H222, H229
Skin Irrit. 2	H315
STOT SE 3	H336
Asp. Tox. 1	H304
Aquatic Acute 1	H400
Aquatic Chronic 1	H410

### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Based on product data or assessment
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REG\_EU / EN