

Rubia SX 40

Engine Oil

KEY DATA



Monograde mineral lubricants, suitable for hydraulic circuits, engines and gearboxes of trucks, agricultural equipments, earthmoving or quarries machinery.

INTERNATIONAL STANDARDS

🔥 API CF / SF

APPLICATIONS

All Hydraulic circuits, Gearboxes and Engines when the manufacturer requires a monograde "Engine oil" type lubricant.

The viscosity grade has to be chosen according to the following table :

HT = High ambient Temperature (> 40°C)

LT = Low ambient Temperature (< -25°C)

PERFORMANCES & CUSTOMER BENEFITS

- 💧 Rubia SX formulations exhibit good thermal stability ensuring efficient lubrication in normal working conditions, without any deposits or varnishes on Hydraulic valves, gears or hot engine parts.
- 💧 Thanks to the high quality of its components, Rubia SX series represent a very cost effective choice without compromising on the technical performances.
- 💧 Its reinforced Base Number (TBN) together with high quality base oils allow a possible extension of the drain interval in Engines, in
- 💧 Hydraulic circuits and in Gearboxes, compared to other classical single grades.
- 💧 Its very low Pour Point makes it possible the immediate start of the machinery, even under very low temperature.
- 💧 Its good filterability provides a fast lubrication of the components, when starting.

CHARACTERISTICS*

RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

This can be obtained on request from your local reseller and is available for consultation at <https://ms-sds.totalenergies.com>.

This product should not be used for any purposes other than the ones for which it is intended.

