










## Engine

### Tractagri

<b>S5R</b> 10W-40	API CK-4 ACEA E4, E6, E7, E9	
<b>S5R FE</b> 5W-30	API CK-4 ACEA E4, E6, E7, E9	 
<b>HDZ</b> 10W-40	API CK-4/SN ACEA E7, E9	
<b>HDZ FE</b> 10W-30	API CK-4 ACEA E7, E9	 
<b>HDZ</b> 15W-40	API CK-4/SN ACEA E7, E9	
<b>HDX</b> 15W-40	API CI-4/SL ACEA E7	
<b>HDX FE</b> 10W-30	API CI-4 ACEA E7	
<b>HDM</b> 15W-40	API SG/CF-4	

## Hydraulic

<b>Hydroflo CT</b> ISO VG: 46	ISO 6743-4 HV DIN 51524-3 HVLP
<b>Hydragri</b> ISO VG: 46-68	ISO 6743-4 HV DIN 51524-3 HVLP
<b>Biohydran SE</b> ISO VG: 32-46-68	ISO 15380: HEES DIN 51524

## Transmissions

### Dynatrans

<b>UTTO</b>	
<b>VZ FE</b>	API GL-4 Synthetic technology UTTO Cold flow properties
<b>MPX</b>	API GL-4 Wide range of application Kubota recommended
<b>MPV</b>	API GL-4 Wide range of application
<b>LS</b> 20W-40	API GL-4 High viscosity for hotter climates
<b>CVT</b> 10W-30	API GL-4 Continuously variable transmission
<b>FR</b>	API GL-4 Graphite brake discs
<b>WS</b> 75W-90   ISO VG: HV 100	API GL-4 Fully synthetic UTTO Extreme temperatures (PAO based)
<b>Biotrans FX</b>	API GL-4   ISO 15380 : HEES

### Axles

<b>DA</b> 80W-90/85W-140	API GL-5 LS Limited slip/ self locking axles
<b>LS</b> 80W-90	API GL-5 LS Limited slip differentials/ self locking axles
<b>HD</b> 80W-90/85W-140	API GL-5 Heavy loaded axles: axles, hypoid and reduction gearboxes
<b>Biotrans LS FE</b> 75W-90	API GL-5 LS

## Grease

### A-Grease

<b>Classic</b> NLGI GRADE: 2	ISO 6743-9: L-XBCEB 2 DIN 51502: KP2K -20
<b>Fil EP 2</b> NLGI GRADE: 2	ISO 6743-9: L-XBCEB 2 DIN 51502: KP2K -25
<b>Complex HV 2</b> NLGI GRADE: 2	ISO 6743-9: L-XBEHB 2 DIN 51502: KP2P -30

## STOU

### Multagri


<b>PRO-TEC</b> 10W-40	API CG-4/SF API GL-4 ACEA E3
<b>MS</b> 15W-40	API CF-4/SF API GL-4 ACEA E2

## Gardening & Chainsaw

### Prosylva

<b>2T Z</b>	ISO L-EGB (PROSYLVA 2T Z) API TC JASO FB
<b>2T SYN</b>	API TC JASO FD ISO L-EGC/EGD
<b>4T</b> 15W-40	API SG/CF-4
<b>4T SYN</b> 10W-40	API SL ACEA A3/B4

### Prosylva Chain

<b>Classic</b>	ISO VG 100
<b>Expert</b>	ISO VG 150
<b>Extrem</b>	ISO VG 220
<b>Chainbio</b>	ISO VG 100 

## Others

<b>Agritraite</b>	ISO VG 68
<b>Vacuum Pump Oil</b>	ISO VG 220
<b>Coolagri Organic - 37°C</b>	AFNOR NFR 15-601 ASTM D3306/D4656/D4985/D6210 BS 6580 SAE J 1034

# Main Agri ranges at a glance



**TotalEnergies**



 [lubricants.totalenergies.com](http://lubricants.totalenergies.com)