

## NEPTUNA 2T BIO-JET

Biodegradable gasoline engine oil

### KEY DATA



✓ Leisure crafts

### SPECIFICATIONS AND APPROVALS

#### International Specifications:

API TC  
NMMA TC-W3®

#### Manufacturers' Approval:

✓ MSR ENGINES: JetSurf Motorized Surfboards

#### Suitable for:

✓ BOMBARDIER  
✓ EVINRUDE  
✓ JOHNSON  
✓ KAWASAKI  
✓ MERCURY  
✓ SEA-DOO  
✓ SUZUKI  
✓ YAMAHA

## APPLICATIONS

TOTAL NEPTUNA 2T BIO-JET is a **synthetic** lubricant suitable for **all 2 strokes gasoline engines**, even when used for competition.

The mixing with the fuel should be in accordance with the manufacturer's recommendations.

TOTAL NEPTUNA 2T BIO-JET combines **protection of the environment** with high performance.

## PERFORMANCES AND CUSTOMER BENEFITS

TOTAL NEPTUNA 2T BIO-JET is **biodegradable** in natural environment. It complies with local regulation requiring this lubricant.

This lubricant is completely **miscible** with gasoline and produces a **homogeneous** and **stable mixture** even at low temperature. It can be used for in-line mixing.

TOTAL NEPTUNA 2T BIO-JET ensures **excellent lubrication** at extreme temperatures.

No exhaust smoke thanks to the **complete combustion** of TOTAL NEPTUNA 2T BIO-JET. Its ash-free formulation helps prevent the clogging of piston ports, avoids spark plug fouling and extends engine lifespan.

Its **anti-rust and anti-corrosion properties** protect engine internal components.

## NEPTUNA 2T BIO-JET

Biodegradable gasoline engine oil

### PHYSICAL AND CHEMICAL CHARACTERISTICS \*

TEST	UNIT	TEST METHOD	VALUE
Kinematic Viscosity at 100 °C	mm <sup>2</sup> /s	ASTM D445	8.4
Pour Point	°C	ASTM D97	< -39
Biodegradability	%	CEC L33-A-93	82
Color			Blue

\* The features mentioned above are average values obtained with some variability in production and do not constitute a specification.

### RECOMMENDATIONS FOR USE

Before using the product, it is important to check the service manual of the vehicle: the drain is carried out according to the manufacturer's requirements.

The product should not be stored at a temperature above 60 °C.

Exposure to strong sunlight, extreme cold or high temperature variations must be avoided. All packages should be protected from bad weather conditions.

The drums should be stored horizontally to avoid a possible contamination by water and the damage of the product label.

### HEALTH, SAFETY AND THE ENVIRONMENT

Based on available information, this product does not cause adverse health effects when used in the intended application and the recommendations provided in the Safety Data Sheet (MSDS) are followed.

It is accessible on request from your local dealer or on the website <http://sdstotalms.total.com>.

This product should not be used for applications other than those for which it is intended. If disposing of used product, take care to protect the environment and comply with local regulations.