

PERFORMANCE S10

Monograde lubricant for **hydraulic applications**.

SPECIFICATIONS AND APPROVALS

International specifications

API CF/SF

APPLICATIONS

Performance S10 is a **mineral** lubricant recommended for **hydraulic systems** and **transmissions**. This lubricant is particularly adapted to **on-road** and **off-road applications**: construction, mining, agriculture.

PERFORMANCES AND CUSTOMER BENEFITS

Performance S10 retains **excellent anti-wear protection**.

Its **anti-rust and anti-corrosion properties** protect the hydraulic circuit components and ensure long equipment life.

Performance S10 exhibits **good resistance to oxidation**, avoiding oil thickening and preventing the formation of deposits and varnishes.

PHYSICAL AND CHEMICAL CHARACTERISTICS*

Performance S10

		Method	Value
Density at 15°C	kg/m ³	ASTM D1298	881
Kinematic Viscosity at 40°C	mm ² /s	ASTM D445	34
Kinematic Viscosity at 100°C	mm ² /s	ASTM D445	5.8
Viscosity Index	-	ASTM D2270	112
Flash point	°C	ASTM D92	>220
Pour point	°C	ASTM D97	-33
T.B.N	mgKOH/g	ASTM D2896	11
Sulphated Ash	% m/m	ASTM D874	1.54

* The features mentioned above are average values obtained with some variability in production and do not constitute a specification.

RECOMMENDATIONS

Before using the product, it is important to check the service manual of the vehicle: the drain is carried out according to the manufacturer's requirements.

The product should not be stored at a temperature above 60 °C. Exposure to strong sunlight, extreme cold or high temperature variations must be avoided.

All packages should be protected from bad weather conditions. The drums should be stored horizontally to avoid a possible contamination by water and the damage of the product label.

HEALTH, SAFETY AND ENVIRONMENT

Based on available information, this product does not cause adverse health effects when used in the intended application and the recommendations provided in the Safety Data Sheet (MSDS) are followed. It is accessible on request from your local dealer or on the website www.finol.ie

This product should not be used for applications other than those for which it is intended.

If disposing of used product, take care to protect the environment and comply with local regulations.