

## AGRIWORX MILKING MACHINE OIL MMO 68

### APPLICATIONS

AgriworX Milking Machine Oil (MMO) is an ISO VG 68, fully inhibited quality oil suitable for milking machines and vacuum pumps.

### SPECIFICATIONS

AFNOR E 48-603 HM. CINCINNATI MILACRON P.68, P.69, P.70, COMMERCIAL HYDRAULICS (EXCEPT FOR PM-500), DENISON HF0, HF-1, HF-2, DIN 51524 P2 HLP, ISO6743/4 HV, RACINE, VARIABLE VOLUME VANE PUMPS, VICKERS M-2950S, I-286.

### ADVANTAGES

- High viscosity index ensures low temperature fluidity.
- Resistance to oxidation protects pump components and valve mechanisms from harmful lacquer deposits.
- Anti-rust and anti-corrosion additives protect the system when at rest.
- Good air release and anti-foaming additives ensure rapid collapse of foam likely to be formed in reservoirs.
- Good demulsification ensures separation of any entrained water droplets.

### TYPICAL CHARACTERISTICS

Properties	Method	Unit	Typical
ISO Viscosity Grade			68
Viscosity index	ISO 2909		100
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	67.5
Pour Point	IP 15	°C	-21
Cleveland flash point	ISO 2592		242
Relative Density @ 15.6°C	IP 160		0.884
Copper Corrosion 3 hours	@ 100°C		1A
Rust Prevention	IP35	Distilled Water	Pass
Rust Prevention	IP35	Salt Water	Pass