

## AGRIWORX SUPER UNIVERSAL SUTO 10W-30

### APPLICATIONS

AgriworX Super Universal SUTO 10W-30 is a multi-purpose oil for use with older agricultural tractors that are operating under normal service conditions. Recommended for tractors pre 1995 and some applications in public works /off-highway construction equipment (excluding those with CVT's).

### SPECIFICATIONS

ACEA E3, API CG-4 / SF, API GL-4.  
ALLISON C4, CATERPILLAR TO-2,  
FORD M2C 159-B/C, FORD M2C 86-B/M2C 134-D  
JD JDM J27, JDM J20C,  
MF: CMS M1145 / M1144 / M1143 / M1139 / M1135 / M1127A,  
ZF TE-ML 03A / 06B / 07B / 07D.

### ADVANTAGES

AgriworX Super Universal Suto 10w30 can reduce the number of lubricants needed on a farm. It exhibits lots of advantages and properties including:

- High viscosity when hot, guaranteeing continuous lubrication in the engine and on gears and hydraulic components
- Low viscosity when cold, for appropriate engine operation in the Nordic regions and easy starting, as well as quick reacting hydraulics
- Outstanding anti-wear properties ensuring longer mechanical components durability
- Extreme-pressure properties allow lubrication of transmissions requiring oil type API GL4 or MIL.L.2105 SAE 80W
- Anti-corrosion additives protect the non-ferrous metals in the engine and other systems.
- Excellent anti-foaming properties, to prevent any sump overflow or cavitation
- Completely inert to seals
- High resistance to oxidation, preventing the formation of deposits and glaze on parts operating at high temperature
- Special frictional characteristics ensuring progressive, efficient and silent operation of brake and clutch systems  
Enhanced anti-squawk properties providing superior wet brake performance.

### TYPICAL CHARACTERISTICS

Test	units	Method	value
Kinematic Viscosity at 40°C	mm <sup>2</sup> /s	ASTM D 445	69
Kinematic Viscosity at 100°C	mm <sup>2</sup> /s	ASTM D 445	10.8
Kinematic Viscosity at 15 °C	Kg/m <sup>3</sup>	ASTM D 1298	878
Viscosity Index	-	ASTM D 2270	146
Pour point	°C	ASTM D 97	-39

The features mentioned above are average values obtained with some variability in production and do not constitute a specification

The product should not be stored at a temperature above 60 °C. Exposure to strong sunlight, extreme cold or high temperature variations must be avoided.

All packages should be protected from bad weather conditions. The drums should be stored horizontally to avoid a possible contamination by water and the damage of the product label

FINOL 2021

