

# AGRIWORX TRACTORFLUID HI-TECH 10W-40

## APPLICATIONS

AGRIWORX Tractor fluid Hi-Tech 10W-40 is an advanced, high-performance, semi-synthetic transmission oil designed for use in the latest agricultural machinery. This grade is primarily for the backends of Massey Ferguson's and Fendt's post 2010. It is also recommended for use in the majority of other public works / off-highway construction equipment.

## SPECIFICATIONS

API GL-4

ALLISON C4 ANFOR NFE 68603 E,

CATERPILLAR TO2

FORD M2C134-D JDM J20C,

MASSEY FERGUSON CMS M 1145 M 1144 / M1143,

ZF TE-ML 03A /06B / 06C / 07B / 07D

## ADVANTAGES

- Suitable for transmissions, hydraulic systems,
- Final drives, wet brakes and oil immersed clutches
- Exceptional wear protection
- Enhanced anti-squawk properties providing superior wet brake performance
- Improved low temperature stability
- Meets a variety of OEM requirements
- Suitable for a wide range of off highway machinery requirements

**TYPICAL CHARACTERISTICS**

Test	units	Method	value
Specific Gravity @ 15.6°C	mm <sup>2</sup> /s	ASTM D 445	0.870
Kinematic Viscosity at 100°C	mm <sup>2</sup> /s	ASTM D 445	13.4
Flash Point COC(°C)	Kg/m <sup>3</sup>	ASTM D 1298	230
Viscosity Index	-	ASTM D 2270	146
TBN (mg KOH/g)			11.6

The features mentioned above are average values obtained with some variability in production and do not constitute a specification

The product should not be stored at a temperature above 60 °C. Exposure to strong sunlight, extreme cold or high temperature variations must be avoided.

All packages should be protected from bad weather conditions. The drums should be stored horizontally to avoid a possible contamination by water and the damage of the product label

**FINOL 2021**