

AGRIWORX TRACTORFLUID BF 16 UTTO

APPLICATIONS

AGRIWORX TRACTORFLUID BF 16 UTTO is a highly versatile, synthetic based lubricant developed for transmissions with wet brakes requiring an API GL-4 80w or an SAE 10W-30 viscosity grade. Used primarily in agricultural equipment and in public works / off-highway construction equipment post 1995 (excluding those with CVT's).

SPECIFICATIONS

API GL-4 80W SAE 10W-30.

AGCO / ALLIS 821 XL, ALLISON C4, CASE MS 1209 MS 1207
CATERPILLAR TO2, CLAAS RENAULT AGRICULTURE CNH
MAT 3505 / 3509 / 3525 / 3526 / 3540
FORD M2C 134-D FNHA 2C 201.00,
JOHN DEERE JDM J20C,
KOMATSU AXO 80, KUBOTA UDT
MF CMS M 1145 / M1143 / M1141 / M1139
MC CORMICK HTX,
NH 410C / 410 B VALTRA G2-08,
VOLVO CE WB 101,
ZF TE-ML 03E / 03L / 05F / 06P / 17E / 21F

ADVANTAGES

AGRIWORX TRACTORFLUID BF 16 UTTO has been especially developed for transmissions with wet brakes requiring an API GL-4 lubricant with a 10W-30 or 80W viscosity grade, in both Off-Road and On-Road vehicles. This lubricant is also perfectly adapted to automatic transmissions, torque converters and hydrostatic transmissions and more generally to any transmissions requiring an UTTO (Universal Tractor Transmissions Oil) lubricant. And is also designed to lubricate hydraulic systems, power-assisted steering and power-take-offs (PTO) with wet clutches.

TYPICAL CHARACTERISTICS

Test	units	Method	value
Kinematic Viscosity at 40°C	mm ² /s	ATSM D 445	64
Kinematic Viscosity at 100°C	mm ² /s	ASTM D 445	10.4
Viscosity Index		ASTM D 2270	150
Pour point	°C	ASTM D 97	-39

The features mentioned above are average values obtained with some variability in production and do not constitute a specification

The product should not be stored at a temperature above 60 °C. Exposure to strong sunlight, extreme cold or high temperature variations must be avoided.

All packages should be protected from bad weather conditions. The drums should be stored horizontally to avoid a possible contamination by water and the damage of the product label

FINOL 2021

