

## PREMIUM BLUE READY TO USE

### Product Description:

CoolTemp Premium Blue Pre-Diluted Ready to use Mono Ethylene Glycol based grade containing no Nitrates, Amines or Phosphates i.e. (NAP Free)

It's suitable for use in Older Diesel Engines found in On-Highway, Agricultural and Off-Highway Construction equipment and also suitable for Petrol & Diesel passenger vehicle engines.

### SPECIFICATIONS

#### INTERNATIONAL

AFNOR NF R 15-601, ASTM D3306, ASTM D4985, BS 6580 (2010), SAE J 1034

### Typical Test Data:

Appearance	Blue liquid	
Density at 20 °C	1.125g/cm <sup>3</sup>	ASTM D 4052
pH (50% vol in water)	8.9	ASTM D 1287
Freezing Point (50% vol in Water)	-37°C	ASTM D 1177
Boiling Point	169°C	ASTM D 1120
Reserve Alkalinity (ml HCl N/10)	21.5ml	ASTM D 1121
Water Content	3% wt	ASTM D 1123
Foaming Characteristics at 88 °C		ASTM D 1881
Height	35 ml	
Breaktime	2.s	

### Storage and Handling

Coolant/Antifreeze has a shelf life of at minimum two years when stored in air-tight containers at a maximum temperature of 30°C. Translucent containers should not be stored outside in direct sunlight, especially in warm climates. Coolant can be stored in mild steel, lacquer lined or HDPE containers. As with any glycol-based engine coolant the use of galvanized steel is not recommended for pipes or any other part of the storage/mixing installation. Disposal of used or unused coolant must be carried out in accordance with local and national law, consult the material safety data sheet for further information.