



FINOL GEAR OIL RANGE

Mineral oil based GL-5 gear oils

Product code: Refer to table below

Product Description:

Finol multigrades are universal extreme pressure gear oils meeting the API performance levels GL-5 and GL-4.

Finol multigrade gear oils are manufactured from high quality base oils and high levels of extreme pressure (EP) additives to provide a lubricant with outstanding anti wear protection. They are designed to cope with the increasing demands of today's motoring conditions, which include high shock-load, high torque, and high speed service conditions.

Benefits:

- Excellent oxidation stability
- Outstanding low and high temperature performance
- Suitable for synchromesh gearboxes
- Long service life
- Good protection against rust and corrosion
- High level of wear protection
- Covers API GL-5 and GL-4 offering rationalisation of grades

Application:

Finol multigrade gear oils are suitable for manual gearboxes, including synchromesh, fitted to automotive vehicles, industrial and commercial vehicles.

Product Specification:

API	GL-5, GL-4
Military	Mil-L-2105D

Typical Test Data:

GEAR OIL	80W-90	80W-140	85W-140
Specific Gravity @ 15.6°C	0.890	0.892	0.898
Kinematic Viscosity @ 100°C (cSt)	16.91	26.95	26.39
Kinematic Viscosity @ 40°C (cSt)	168.0	235.5	320.1
Viscosity Index	107	148	109
Flash Point, COC (°C)	220	240	245
Pour Point (°C)	-28	-27	-17

Health & Safety:

Please refer to the safety data sheet, a copy of which is freely available to all of our customers.