



## FINOL GEAR OIL EP 140

### APPLICATIONS

Gear Oil EP 140 is a universal extreme pressure gear oil meeting the API performance level GL 4-GL-5. Finol EP gear oils are manufactured from high quality base oils and high levels of extreme pressure (EP) additives to provide a lubricant with outstanding anti wear protection. They are designed to cope with the increasing demands of today's motoring conditions, which include high shock-load, high torque, and high-speed service conditions.

### SPECIFICATIONS

- GL 4, GL 5
- MIL-L-2105 D

### ADVANTAGES

- Excellent oxidation stability
- Outstanding low and high temperature performance
- Suitable for synchromesh gearboxes
- long service life
- Good protection against rust and corrosion
- High level of wear protection
- Covers API GL-5 and GL-4 offering rationalisation of grades

## TYPICAL CHARACTERISTICS

<b>GEAR OIL EP 140</b>	<b>140 W</b>
<b>Specific Gravity @ 15.6 °C</b>	<b>0.898</b>
<b>Kinematic Viscosity @ 100°C (cSt)</b>	<b>23.69</b>
<b>Kinematic Viscosity @ 40 °C (cSt)</b>	<b>320.1</b>
<b>Viscosity Index</b>	<b>109</b>
<b>Flash Point COC (C)</b>	<b>245</b>
<b>Pour Point (C)</b>	<b>-17</b>

The features mentioned above are average values obtained with some variability in production and do not constitute a specification

Before using the product, it is important to check the service manual of the vehicle: the drain is carried out according to the manufacturer's requirements

The product should not be stored at a temperature above 60 °C. Exposure to strong sunlight, extreme cold or high temperature variations must be avoided.

All packages should be protected from bad weather conditions. The drums should be stored horizontally to avoid a possible contamination by water and the damage of the product label