

XENITH PRO F 5W-30

Fully synthetic, fuel saving engine oil for many Ford vehicles

Product Description:

XENITH PRO F5W-30 is a fully synthetic, fuel-efficient multi grade engine oil meeting the Ford specification WSS-M2C913-D and WSS-M2C913-C, and meeting the STJLR.03.5003 Jaguar / Land Rover specification.

XENITH PRO F 5W-30 is a fully synthetic multi grade engine oil formulated with highly refined synthetic base stocks and the very latest in advanced additive technology. The carefully selected components combine to provide the user with improved fuel economy benefits, greater robustness to fuels containing increased levels of bio diesel and superior soot handling properties. This highly stable, stay-in-grade product allows extended oil drain intervals to be achieved.

Benefits:

- Ford specification WSS-M2C913-D
- Ford specification WSS-M2C913-C
- Extended drain capability
- Fully backwards compatible with the earlier specifications of WSS-M2C 913-A and 913-B
- Stay-in-grade formulation
- Excellent low temperature stability for improved flow rates
- Improved fuel efficiency
- Fully synthetic formulation

Applications:

XENITH PRO F 5W-30 is an ideal choice in many normally aspirated and turbocharged petrol and diesel engines designed to use a fuel saving engine lubricant.

In particular, **XENITH PRO F 5W-30** can be used in all Ford diesel engines (except Ford Ka TDCi 2009 onwards and Galaxy 1.9 TDi 2000-2006). It is strongly recommended for use in Transit models (2012 onwards) carrying the 2.2 Duratorq TDCi engine where only WSS-M2C913-D lubricants can be used.

Product Specification:

ACEA	A5/B5, A1/B1
API	SL/CF
Ford	WSS-M2C913-D WSS-M2C913-C
Jaguar / Land Rover	STJLR.03.5003
Volvo Satisfies	Requirements

Typical Test Data:

Kinematic Viscosity @ 100°C (cSt)	9.53
Kinematic Viscosity @ 40°C (cSt)	51.5
Viscosity Index	172
Flash Point (Closed) (°C)	235
TBN (mg KOH/g)	10.2
Pour Point (°C)	-38