

# XENITH PRO-V 0W-30

## Product Description

XENITH PRO V 0W-30 is an advanced synthetic technology engine oil that has been developed to cover the most stringent requirements of both gasoline and diesel passengers cars engines and it is particularly suited to the most recent engines. This engine oil can be used in the most difficult operating conditions motorways, city traffic., and is appropriate for all driving types and for every season.

## Benefits

- ACEA A3/B4
  - API SL/CF
  - MERCEDES BENZ MB 229.5
  - VOLVO VCC 95200356
  - VW 502.00/505.00
- Suitable for Ford

## Advantages

- Engine Protection and cleanliness and performance
- Anti-wear protection
- Oxidation resistance: allows extra-long drain intervals
- Fuel savings Benefits
- Easier cold starting

### Typical Test Data

|                                   |        |
|-----------------------------------|--------|
| Viscosity Grade                   | 0W -30 |
| Density at 15°C                   | 850    |
| Kinematic Viscosity @ 100°C (cSt) | 12.3   |
| Kinematic Viscosity @ 40°C (cSt)  | 68.7   |
| Viscosity Index                   | 170    |
| Flash Point COC (°C)              | 226    |
| Pour Point (°C)                   | -45    |

The features mentioned above are average values obtained with some variability in production and do not constitute a specification.

Before using the product, it is important to check the service manual of the vehicle: the drain is carried out according to the manufacturer's requirements.

The product should not be stored at a temperature above 60 °C. Exposure to strong sunlight, extreme cold or high temperature variations must be avoided.

All packages should be protected from bad weather conditions. The drums should be stored horizontally to avoid a possible contamination by water and the damage of the product label