

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name : OSYRIS X 9100
Product code : 31245
Product description : Not available.
Product type : Liquid.
Other means of identification : Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Preservatives
anticorrosion

Uses advised against

Not applicable.

1.3 Details of the supplier of the safety data sheet

TotalEnergies Lubrifiants
562 Avenue du Parc de L'île
92029 Nanterre Cedex FRANCE
Tél: +33 (0)1 41 35 40 00
Fax: +33 (0)1 41 35 84 71
rm.msds-lubs@totalenergies.com

TotalEnergies Marketing UK Limited
10 Upper Bank Street (19th floor)
Canary Wharf,
London E14 5BF
UNITED KINGDOM
Tel: +44 (0)20 7339 8000
Fax: +44 (0)20 7339 8033
rm.gb-msds@totalenergies.com

H.S.E

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : National Poisons Information Service (NPIS): 111

Supplier

Telephone number : Emergency telephone: +44 1235 239670

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226

STOT SE 3, H336

Aquatic Chronic 3, H412


The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H226 - Flammable liquid and vapour.
H336 - May cause drowsiness or dizziness.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273 - Avoid release to the environment.
P261 - Avoid breathing gas, vapour or spray.

Response : P312 - Call a POISON CENTER or doctor if you feel unwell.
P370 + P378 - In case of fire: Use alcohol-resistant foam to extinguish.

Storage : P403 + P235 - Store in a well-ventilated place. Keep cool.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Contains : ☒ Hydrocarbon, C9-C11, n-alkane, iso-alkane, cyclic, containing <2% of aromatics, < 0,1% of benzene, < 1% of n-hexane and < 0,5 % of aromatic hydrocarbons
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Supplemental label elements : Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

SECTION 2: Hazards identification

This mixture does not contain any substances that are assessed to be a PBT or a vPvB in a concentration $\geq 0,1\%$.

This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACH Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

Other hazards which do not result in classification : Hazard of slipping on spilt product.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Type
Hydrocarbon, C9-C11, n-alkane, iso-alkane, cyclic, containing <2% of aromatics, < 0,1% of benzene, < 1% of n-hexane and < 0,5 % of aromatic hydrocarbons	REACH #: 01-2119463258-33 EC: 923-037-2 CAS: 64742-48-9*	$\geq 25 - \leq 50$	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304	[1]
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics	REACH #: 01-2119471843-32 EC: 927-241-2 CAS: 64742-48-9*	$\geq 25 - \leq 50$	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 3, H412 EUH066	[1]
Hydrocarbons, C9, aromatics	REACH #: 01-2119455851-35 EC: 918-668-5 CAS: 64742-95-6*	≤ 10	Flam. Liq. 3, H226 STOT SE 3, H335 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066	[1]
Distillates (petroleum), hydrotreated heavy paraffinic	REACH #: 01-2119484627-25 EC: 265-157-1 CAS: 64742-54-7 Index: 649-467-00-8	≤ 10	Asp. Tox. 1, H304 See Section 16 for the full text of the H statements declared above.	[1]

Additional information : Mineral oil of petroleum origin Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

The EC substance definition and related classification & labelling have been developed in the framework of the Regulation (EC) No 1907/2006 (REACH). The related CAS number* is used for the purpose of the international inventories present in section 15 of the SDS.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 3: Composition/information on ingredients

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
irritation
dryness
cracking
- Ingestion** : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

SECTION 4: First aid measures

Specific treatments : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, alcohol-resistant foam or water spray (fog).

Unsuitable extinguishing media : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion products : carbon monoxide
carbon dioxide

5.3 Advice for firefighters

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and material for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

SECTION 6: Accidental release measures

Large spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

6.4 Reference to other sections : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Seveso Directive - Reporting thresholds

Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
P5c	5000 tonne	50000 tonne

7.3 Specific end use(s)

Recommendations : Not available.

SECTION 7: Handling and storage

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

Reportable hazardous constituent(s) contained in UVCB- and/or multi-constituent substance(s) complying with the classification criteria and/or with an exposure limit (OEL)

No exposure limit value known.

Biological Limit Values (BLV)

No exposure indices known.

Recommended monitoring procedures : Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Advisory OEL : Metalworking fluids: USA: NIOSH (REL) TWA 0.5 mg/m³ Mineral oil mist: USA: OSHA (PEL) TWA 5 mg/m³, NIOSH (REL) TWA 5 mg/m³, STEL 10 mg/m³, ACGIH (TLV) TWA 5 mg/m³ (highly refined)

DNELs/DMELs

Product/substance	Type	Exposure	Value	Population	Effects
LOW BOILING POINT NAPHTHAS (GASOLINES) Benzene < 0.1% w/w; Toluene < 3% w/w; n-hexane < 3% w/w; Flashpoint ≥ 23°C and ≤ 60°C	DNEL	Long term Inhalation	1500 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	300 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	900 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	300 mg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	300 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	300 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1500 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	300 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	900 mg/m ³	General population	Systemic
	DNEL	Long term Oral	300 mg/kg bw/day	General population	Systemic
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics	DNEL	Long term Inhalation	150 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	25 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	11 mg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	11 mg/kg bw/day	General population	Systemic
	DNEL	Long term	32 mg/m ³	General	Systemic

SECTION 8: Exposure controls/personal protection

Distillates (petroleum), hydrotreated heavy paraffinic	DNEL	Inhalation Long term Oral	0.74 mg/ kg bw/day	population General population	Systemic
	DNEL	Long term Dermal	0.97 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.19 mg/m ³	General population	Local
	DNEL	Long term Inhalation	2.73 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	5.58 mg/m ³	Workers	Local

PNECs

Product/substance	Compartment Detail	Value	Method Detail
Distillates (petroleum), hydrotreated heavy paraffinic	Secondary Poisoning	9.33 mg/kg	-

8.2 Exposure controls

Appropriate engineering controls

- : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures

- : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

- : ☒ Safety glasses with side-shields, EN 166.

Skin protection

Hand protection

- : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Hydrocarbon-proof gloves

nitrile rubber

Fluorinated rubber

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

In case of prolonged contact with the product, it is recommended to wear gloves complying with ISO 21420 and EN 374 standards, protecting at least for 480 minutes and having a thickness of 0,38 mm at least. These values are indicative only. The level of protection is provided by the material of the glove, its technical characteristics, its resistance to the chemicals to be handled, the appropriateness of its use and its replacement frequency

SECTION 8: Exposure controls/personal protection

- Body protection** : Wear work clothing with long sleeves.
Non-skid safety shoes or boots
- Respiratory protection** : Ensure adequate ventilation and check that a safe, breathable atmosphere is present before entry into confined spaces. In case of inadequate ventilation wear respiratory protection: Type A/P2. Warning ! filters have a limited use duration. The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature (20°C / 68°F) and pressure (1013 hPa) unless otherwise indicated

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid. [Clear]
- Colour** : Black.
- Odour** : Characteristic.
- Melting point/freezing point** : -60°C [ISO 3016]
- Initial boiling point and boiling range** : 140.18°C (284.3°F) [ISO 3405]
- Flammability (solid, gas)** : Not applicable.
- Upper/lower flammability or explosive limits** : Lower: 0.7%
Upper: 6.1%
- Flash point** : Closed cup: >28°C (>82.4°F) [ASTM D 92]
- Auto-ignition temperature** : Not available.
- Decomposition temperature** : Not available.
- pH** : Not applicable. Product is non-soluble (in water).
- Viscosity** : Kinematic (40°C): 60 mm²/s [ISO 3104]
- Solubility(ies)** :

Media	Result
water	Not soluble

- Solubility in water** : 0.89 g/l
- Miscible with water** : No.
- Partition coefficient: n-octanol/ water** : Not applicable.
- Vapour pressure** : <0.013 kPa (<0.1 mm Hg)
- Relative density** : 0.7781 to 0.7855 [EN ISO 12185]
- Density** : 0.7781 to 0.7855 g/cm³ [15°C (59°F)] [EN ISO 12185]
- Vapour density** : Not available.
- Particle characteristics**
- Median particle size** : Not applicable.

SECTION 9: Physical and chemical properties

9.2 Other information

No other relevant physical and chemical parameters for the safe use of the product

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : Stable under recommended storage and handling conditions (see Section 7).

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.

10.5 Incompatible materials : Strong oxidising agents
strong acids
Strong bases

10.6 Hazardous decomposition products : carbon monoxide
carbon dioxide

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/substance	Result	Species	Dose	Exposure	Test
hydrocarbon, C9-C11, n-alkane, iso-alkane, cyclic, containing <2% of aromatics, < 0,1% of benzene, < 1% of n-hexane and < 0,5 % of aromatic hydrocarbons	LD50 Oral	Rat	>6 g/kg	-	-
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics	LC50 Inhalation Vapour	Rat	80.4 mg/l	1 hours	-
	LC50 Inhalation Vapour	Rat	20.1 mg/l	4 hours	-
	LC50 Inhalation Vapour	Rat	>4591 mg/m ³	4 hours	OECD 403
	LD50 Dermal	Rabbit	>5000 mg/kg	-	OECD 402
	LD50 Oral	Rat	>5000 mg/kg	-	OECD 401
Hydrocarbons, C9, aromatics	LC50 Inhalation Vapour	Rat	>6193 mg/l	4 hours	OECD 403
			Maximum Concentration (%):		
	LD50 Dermal	Rabbit	>3160 mg/kg	-	OECD 402
	LD50 Oral	Rat - Male, Female	3592 mg/kg	-	OECD
Distillates (petroleum), hydrotreated heavy paraffinic	LC50 Inhalation Dusts and mists	Rat - Male, Female	>5 mg/l	4 hours	OECD 403 Read across
	LD50 Dermal	Rabbit - Male, Female	>5000 mg/kg	-	OECD 402 Read across

SECTION 11: Toxicological information

	LD50 Oral	Rat - Male, Female	>5000 mg/kg	-	OECD 401 Read across
--	-----------	-----------------------	-------------	---	-------------------------

Acute toxicity estimates

Product/substance	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics	N/A	N/A	N/A	20.1	N/A
Hydrocarbons, C9, aromatics	3592	N/A	N/A	N/A	N/A

Conclusion/Summary : Based on available data, the classification criteria are not met.

Irritation/Corrosion

Conclusion/Summary

Skin : Based on available data, the classification criteria are not met.

Eyes : Based on available data, the classification criteria are not met.

Respiratory : Based on available data, the classification criteria are not met.

Sensitisation

Conclusion/Summary :

Skin : Based on available data, the classification criteria are not met.

Respiratory : Based on available data, the classification criteria are not met.

Mutagenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Carcinogenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Reproductive toxicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Teratogenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Product/substance	Category	Route of exposure	Target organs
LOW BOILING POINT NAPHTHAS (GASOLINES)	Category 3	-	Narcotic effects
Benzene < 0.1% w/w; Toluene < 3% w/w; n-hexane < 3% w/w; Flashpoint ≥ 23°C and ≤ 60°C	Category 3	-	Narcotic effects
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Category 3	-	Respiratory tract irritation
Hydrocarbons, C9, aromatics	Category 3	-	Narcotic effects

Conclusion/Summary : Based on available data, the classification criteria are met.

Specific target organ toxicity (repeated exposure)

Not available.

Conclusion/Summary : Based on available data, the classification criteria are not met.

Aspiration hazard

SECTION 11: Toxicological information

Product/substance	Result
LOW BOILING POINT NAPHTHAS (GASOLINES) Benzene < 0.1% w/w; Toluene < 3% w/w; n-hexane < 3% w/w; Flashpoint ≥ 23°C and ≤ 60°C	ASPIRATION HAZARD - Category 1
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics	ASPIRATION HAZARD - Category 1
Hydrocarbons, C9, aromatics	ASPIRATION HAZARD - Category 1
Distillates (petroleum), hydrotreated heavy paraffinic	ASPIRATION HAZARD - Category 1

Conclusion/Summary : Based on available data, the classification criteria are not met.

Information on likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : Defatting to the skin. May cause skin dryness and irritation.
- Ingestion** : Can cause central nervous system (CNS) depression.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : No specific data.
- Inhalation** : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
irritation
dryness
cracking
- Ingestion** : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Potential chronic health effects

Not available.

- Conclusion/Summary** : Not available.
- General** : No known significant effects or critical hazards.
- Carcinogenicity** : No known significant effects or critical hazards.

SECTION 11: Toxicological information

Mutagenicity : No known significant effects or critical hazards.
Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards


11.2.1 Endocrine disrupting properties

This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACH Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.


11.2.2 Other information

Not available.

SECTION 12: Ecological information

 Harmful to aquatic life with long lasting effects.

12.1 Toxicity

Product/substance	Result	Species	Exposure	Test
 Hydrocarbon, C9-C11, n-alkane, iso-alkane, cyclic, containing <2% of aromatics, < 0,1% of benzene, < 1% of n-hexane and < 0,5 % of aromatic hydrocarbons	Acute EC50 1000 mg/l	Algae - <i>Pseudokirchneriella subcapitata</i>	72 hours	OECD 201
	Acute EC50 1000 mg/l	Daphnia - <i>Daphnia magna</i>	48 hours	OECD 202
	Acute LC50 1000 mg/l	Fish	96 hours	-
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Acute EC50 1000 mg/l	Algae	72 hours	-
	Acute EC50 23 mg/l	Daphnia - <i>Daphnia magna</i>	48 hours	-
	Acute EC50 2.9 mg/l	Algae - <i>Pseudokirchnerella subcapitata</i>	72 hours	OECD 201
Hydrocarbons, C9, aromatics	Acute EC50 3.2 mg/l	Daphnia - <i>Daphnia Magna</i>	48 hours	OECD 202
	Acute LC50 9.2 mg/l	Fish	96 hours	-
	Chronic NOELR 2.14 mg/l	Daphnia - <i>Daphnia Magna</i>	21 days	-
Distillates (petroleum), hydrotreated heavy paraffinic	Chronic NOELR 1.23 mg/l	Fish - <i>Oncorhynchus mykiss</i>	21 days	-
	Acute EC50 >100 mg/l	Algae - <i>Pseudokirchneriella subcapitata</i>	72 hours	OECD 201
	Acute EC50 >10000 mg/l	Crustaceans - <i>Daphnia magna</i>	48 hours	OECD 202
	Chronic NOEL >100 mg/l	Algae - <i>Pseudokirchneriella subcapitata</i>	72 hours	OECD 201
	Chronic NOEL >1000 mg/l	Crustaceans - <i>Daphnia magna</i>	21 days	-

Conclusion/Summary : Not available.

12.2 Persistence and degradability

**SECTION 12: Ecological information**

Product/substance	Test	Result	Dose	Inoculum
Hydrocarbons, C9, aromatics Distillates (petroleum), hydrotreated heavy paraffinic	OECD 301 F OECD 301F	78 % - Readily - 28 days 31 % - Not readily - 28 days	- -	- Activated sludge

Conclusion/Summary : Not available.

Product/substance	Aquatic half-life	Photolysis	Biodegradability
Hydrocarbons, C9-C10, n- alkanes, isoalkanes, cyclics, < 2% aromatics	-	-	Readily
Hydrocarbons, C9, aromatics Distillates (petroleum), hydrotreated heavy paraffinic	- -	- -	Readily Not readily

12.3 Bioaccumulative potential

Product/substance	LogP _{ow}	BCF	Potential
LOW BOILING POINT NAPHTHAS (GASOLINES) Benzene < 0.1% w/w; Toluene < 3% w/w; n- hexane < 3% w/w; Flashpoint ≥ 23°C and ≤ 60°C	-	10 to 2500	High
Hydrocarbons, C9, aromatics Distillates (petroleum), hydrotreated heavy paraffinic	4.73 >4	- -	High High

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

Mobility in soil : Given its physical and chemical characteristics, the product generally shows low soil mobility. The product is insoluble and floats on water. Loss by evaporation is limited. Forms an emulsion.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB in a concentration ≥ 0,1 %.

12.6 Endocrine disrupting properties

This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACH Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.





Hazardous waste : Yes.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used. The following Waste Codes are only suggestions: 12 01 07*

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ICAO/IATA
14.1 UN number or ID number	UN1268	UN1268	UN1268	UN1268
14.2 UN proper shipping name	PETROLEUM DISTILLATES, N.O.S.	PETROLEUM DISTILLATES, N.O.S.	PETROLEUM DISTILLATES, N.O.S.	Petroleum distillates, n.o.s.
14.3 Transport hazard class(es)	3 	3 	3 	3 
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	No.	Yes.	No.	No.

Additional information

SECTION 14: Transport information

ADR/RID	: Hazard identification number 30 Limited quantity 5 L Special provisions 664 Tunnel code (D/E)
ADN	: The product is only regulated as an environmentally hazardous substance when transported in tank vessels.
IMDG	: Emergency schedules F-E, S-E Special provisions 223, 955
IATA	: Quantity limitation Passenger and Cargo Aircraft: 60 L. Packaging instructions: 355. Cargo Aircraft Only: 220 L. Packaging instructions: 366. Limited Quantities - Passenger Aircraft: 10 L. Packaging instructions: Y344. Special provisions A3

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
UK (GB)/REACH

Annex XIV - List of substances subject to authorisation
Annex XIV

None of the components are listed.

Substances of very high concern
None of the components are listed.

Ozone depleting substances
Not listed.

Prior Informed Consent (PIC)
Not listed.

Persistent Organic Pollutants
Not listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category

P5c

EU regulations

SECTION 15: Regulatory information

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

DIRECTIVE 2008/68/EC related on the inland transport of dangerous goods

**Industrial emissions
(integrated pollution
prevention and control) -
Air** : Not listed

**Industrial emissions
(integrated pollution
prevention and control) -
Water** : Not listed

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia inventory (AIIC)	: All components are listed or exempted.
Canada inventory	: All components are listed or exempted.
China inventory (IECSC)	: All components are listed or exempted.
Europe inventory	: All components are listed or exempted.
Japan inventory	: Japan inventory (CSCL) : All components are listed or exempted. Japan inventory (ISHL) : Not determined.
New Zealand Inventory of Chemicals (NZIoC)	: All components are listed or exempted.
Philippines inventory (PICCS)	: All components are listed or exempted.
Korea inventory (KECI)	: All components are listed or exempted.
Taiwan Chemical Substances Inventory (TCSI)	: Not determined.
Thailand inventory	: Not determined.
Turkey inventory	: Not determined.
United States inventory (TSCA 8b)	: All components are listed or exempted.
Vietnam inventory	: Not determined.

The information stated in this section relates solely to the conformity of the chemical product with the countries Inventories. The information used to confirm the inventory status of this product may be based on additional data to the chemical composition shown in Section 3. Other regulations may apply for importation or marketing authorizations.

SECTION 15: Regulatory information

15.2 Chemical safety assessment : Risk management measures and safety conditions of use are included in the relevant sections of the SDS

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms :

- ATE = Acute Toxicity Estimate
- CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
- DNEL = Derived No Effect Level
- DMEL = Derived Minimal Effect Level
- EUH statement = CLP-specific Hazard statement
- N/A = Not available
- PBT = Persistent, Bioaccumulative and Toxic
- vPvB = Very Persistent and Very Bioaccumulative
- PNEC = Predicted No Effect Concentration
- LC50 = Median lethal concentration
- LD50 = Median lethal dose
- OEL = Occupational Exposure Limit
- VOC = Volatile Organic Compound
- UVCB Substance of unknown or Variable composition, Complex reaction products or Biological material
- NOEC No Observed Effect Concentration
- QSAR = Quantitative Structure–Activity Relationship

Procedure used to derive the classification

Classification	Justification
Flam. Liq. 3, H226 STOT SE 3, H336 Aquatic Chronic 3, H412	On basis of test data Calculation method Calculation method

Full text of abbreviated H statements

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Full text of classifications

Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

Date of printing : 2023/07/31

Date of issue/ Date of revision : 2023/07/31

Date of previous issue : 2023/02/02

Version : 4

Notice to reader

SECTION 16: Other information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.