

FLUIDE DA

Synthetic hydraulic fluid

KEY DATA

XXXXX

MEETS THE REQUIREMENTS OF

- 🔥 MAN 3289
- 🔥 PSA S71 2710

APPLICATIONS

Synthetic fluid of orange colour for the hydraulic system of Citroën cars equipped with “HYDRActive 3”
Do not use when a mineral fluid of fluo green colour is requested (LHM Plus)

PERFORMANCES & CUSTOMER BENEFITS

- 🔥 Super multigrade fluid
- 🔥 Exceptionally high viscosity index
- 🔥 Very low pour point
- 🔥 Very high thermal stability
- 🔥 Very good protection against wear and corrosion
- 🔥 Excellent lubricating properties

CHARACTERISTICS *

TEST	UNIT	TEST METHOD	RESULT
Density at 15°C	kg/m3	ASTM D 1298	820
Kinematic viscosity at 40°C	mm ² /s	ASTM D445	18
Kinematic viscosity at 100°C	mm ² /s	ASTM D445	5.9
Viscosity index	-	ASTM D2270	320
Pour point	°C	ASTM D97	-51
Flash Point	°C	ASTM D92	157

* The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

This can be obtained on request from your local reseller and is available for consultation at <https://ms-sds.totalenergies.com>.

This product should not be used for any purposes other than the ones for which it is intended.



TotalEnergies Lubricants / Last update of this datasheet: June 23 / FLUDIE DA

Some variations can be expected under normal production conditions, but these should not affect the product's expected performance irrespective of the site. The information contained in this document is subject to change without notice. Our products can be viewed on our website at www.lubricants.totalenergies.com.