

Mineral lubricant suitable for **diesel engines**.

SPECIFICATIONS AND APPROVALS

International specifications

API: CE/SG CATERPILLAR T02

APPLICATIONS

Performance S30 is a **mineral** lubricant recommended for **old diesel engines** of **transport, public works materials, agricultural vehicles, lawnmowers**

It is also suitable for **stationary engines**.

Performance S30 is suitable for all diesel engines when an **SAE 30 grade lubricant** is **recommended**.

PERFORMANCES AND CUSTOMER BENEFITS

Performance S30 exhibits **good resistance to oxidation**, preventing the formation of deposits and varnishes.

Detergent, dispersant and anti-wear properties keep the **engine clean** and enable effective control of soot, sludge and piston deposits.

PHYSICAL AND CHEMICAL CHARACTERISTICS*

Performance S30

		Method	Value
Density at 15°C	kg/m ³	ASTM D1298	895
Kinematic Viscosity at 40°C	mm ² /s	ASTM D445	103
Kinematic Viscosity at 100°C	mm ² /s	ASTM D445	11.5
Viscosity Index	-	ASTM D2270	98
Flash point	°C	ASTM D92	>220
Pour point	°C	ASTM D97	-24
T.B.N	mgKOH/g	ASTM D2896	11
Sulphated Ash	% m/m	ASTM D874	1.52

* The features mentioned above are average values obtained with some variability in production and do not constitute a specification.

RECOMMENDATIONS

Before using the product, it is important to check the service manual of the vehicle: the drain is carried out according to the manufacturer's requirements.

The product should not be stored at a temperature above 60 °C. Exposure to strong sunlight, extreme cold or high temperature variations must be avoided.

All packages should be protected from bad weather conditions. The drums should be stored horizontally to avoid a possible contamination by water and the damage of the product label.

HEALTH, SAFETY AND ENVIRONMENT

Based on available information, this product does not cause adverse health effects when used in the intended application and the recommendations provided in the Safety Data Sheet (MSDS) are followed. It is accessible on request from your local dealer or on the website www.finol.ie

This product should not be used for applications other than those for which it is intended.

If disposing of used product, take care to protect the environment and comply with local regulations.