SAFETY DATA SHEET



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

QUARTZ INEO RCP 5W-30

SDS#: C3I2EIDG4

previous revision date : 2023/07/19

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : QUARTZ INEO RCP 5W-30

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Engine oil

1.3 Details of the supplier of the safety data sheet

TotalEnergies Lubrifiants 562 Avenue du Parc de L'ile 92029 Nanterre Cedex FRANCE Tél: +33 (0)1 41 35 40 00 Fax: +33 (0)1 41 35 84 71

rm.msds-lubs@totalenergies.com

TotalEnergies Marketing Norge AS

Finnestadveien 44, N-4029 Stavanger,

Norge

Tlf. +47 22019559

sm.nordic-reach@totalenergies.com

Contact

H.S.E

1.4 Emergency telephone number

National advisory body/Poison Center

Telephone number: Poisoning Information: +472 259 1300

Supplier

Telephone number: Emergency phone: +44 1235 239670

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 11 for more detailed information on health effects and symptoms.

 Revision:2023/10/17
 Version : 1.01
 Norway
 ENGLISH
 1/20



SDS #: C3I2EIDG4

2.2 Label elements

Signal word : No signal word.

Hazard statements : No known significant effects or critical hazards.

Precautionary statements

Prevention : Not applicable. Response : Not applicable. Storage : Not applicable. **Disposal** : Not applicable.

Supplemental label

elements

: Contains C14-16-18 Alkyl phenol. May produce an allergic reaction.

Safety data sheet available on request.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

: Not applicable.

2.3 Other hazards

This mixture does not contain any substances that are assessed to be a PBT or a vPvB in a concentration >= 0,1 %. This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACh Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

Other hazards which do

: Hazard of slipping on spilled product.

not result in classification

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/substance	Identifiers	% (w/w)	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Distillates (petroleum), hydrotreated heavy paraffinic	REACH #: 01-2119484627-25 EC: 265-157-1 CAS: 64742-54-7 Index: 649-467-00-8	≤5	Asp. Tox. 1, H304	-	[1] [2]
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	REACH #: 01-2119474878-16 EC: 276-737-9 CAS: 72623-86-0 Index: 649-482-00-X	≤3	Asp. Tox. 1, H304	-	[1] [2]
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	REACH #: 01-2119474889-13 EC: 276-738-4 CAS: 72623-87-1 Index: 649-483-00-5	≤3	Asp. Tox. 1, H304	-	[1] [2]
Distillates (petroleum), solvent-dewaxed heavy paraffinic	REACH #: 01-2119471299-27 EC: 265-169-7 CAS: 64742-65-0 Index: 649-474-00-6	≤3	Asp. Tox. 1, H304	-	[1] [2]

Revision:2023/10/17 Version: 1.01 **ENGLISH** 2/20 Norway



SDS #: C3I2EIDG4

Distillates (petroleum), solvent-dewaxed light paraffinic	REACH #: 01-2119480132-48 EC: 265-159-2 CAS: 64742-56-9 Index: 649-469-00-9	≤3	Asp. Tox. 1, H304	-	[1] [2]
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert- butyl-4-hydroxyphenyl) propionate	REACH #: 01-0000015551-76 EC: 406-040-9 CAS: 125643-61-0	≤3	Aquatic Chronic 4, H413	-	[1]
Paraffin oils (petroleum), catalytic dewaxed heavy	REACH #: 01-2119487080-42 EC: 265-174-4 CAS: 64742-70-7	≤3	Asp. Tox. 1, H304	-	[1] [2]
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	REACH #: 01-2119491299-23 EC: 270-128-1 CAS: 68411-46-1	≤1	Repr. 2, H361f	-	[1]
C14-16-18 Alkyl phenol	REACH #: 01-2119498288-19 EC: 931-468-2	≤0.3	Skin Sens. 1B, H317 STOT RE 2, H373	-	[1]
			See Section 16 for the full text of the H statements declared above.		

Additional information

: Mineral oil of petroleum origin. Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Check for and remove any contact lenses. Get medical attention if irritation

occurs.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Get medical attention if symptoms occur.

Skin contact: Wash skin thoroughly with soap and water or use recognized skin cleanser.

Remove contaminated clothing and shoes. Get medical attention if symptoms occur.

Ingestion : ₩ash out mouth with water. Do not induce vomiting unless directed to do so by

medical personnel. Get medical attention if symptoms occur.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact : No specific data.



SDS #: C3I2EIDG4

Inhalation : No specific data.

Skin contact : Adverse symptoms may include the following:

> irritation dryness cracking

Ingestion : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing

media

: Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing

media

: Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous combustion

products

: carbon monoxide carbon dioxide nitrogen oxides phosphorus oxides sulfur oxides Hydrogen sulfide Mercaptans Zinc oxides

5.3 Advice for firefighters

Special protective actions

for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without

suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Revision:2023/10/17 Version: 1.01 **ENGLISH** 4/20 Norway



SDS#: C3I2EIDG4

6.2 Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other sections

: See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8).

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional

information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific : Not available.

solutions

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Product/substance	Exposure limit values
istillates (petroleum), hydrotreated heavy paraffinic	FOR-2011-12-06-1358 (Norway, 6/2021). [Oil mist (mineral oil particles)]
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	TWA: 1 mg/m³ 8 hours. Form: mineral oil particles FOR-2011-12-06-1358 (Norway, 6/2021). [Oil vapor] TWA: 50 mg/m³ 8 hours. Form: vapor FOR-2011-12-06-1358 (Norway, 6/2021). [Oil mist (mineral oil particles)] TWA: 1 mg/m³ 8 hours. Form: mineral oil particles

 Revision:2023/10/17
 Version : 1.01
 Norway
 ENGLISH
 5/20



SDS #: C3I2EIDG4

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based

FOR-2011-12-06-1358 (Norway, 6/2021). [Oil vapor]
TWA: 50 mg/m³ 8 hours. Form: vapor
FOR-2011-12-06-1358 (Norway, 6/2021). [Oil mist (mineral oil

particles)]

TWA: 1 mg/m³ 8 hours. Form: mineral oil particles FOR-2011-12-06-1358 (Norway, 6/2021). [Oil vapor]

TWA: 50 mg/m³ 8 hours. Form: vapor

Distillates (petroleum), solvent-dewaxed heavy paraffinic

FOR-2011-12-06-1358 (Norway, 6/2021). [Oil mist (mineral oil particles)]

TWA: 1 mg/m³ 8 hours. Form: mineral oil particles **FOR-2011-12-06-1358 (Norway, 6/2021). [Oil vapor]** TWA: 50 mg/m³ 8 hours. Form: vapor

Distillates (petroleum), solvent-dewaxed light paraffinic

FOR-2011-12-06-1358 (Norway, 6/2021). [Oil mist (mineral oil particles)]

TWA: 1 mg/m³ 8 hours. Form: mineral oil particles FOR-2011-12-06-1358 (Norway, 6/2021). [Oil vapor]

TWA: 50 mg/m³ 8 hours. Form: vapor

Paraffin oils (petroleum), catalytic dewaxed heavy

with the classification criteria and/or with an exposure limit (OEL)

FOR-2011-12-06-1358 (Norway, 6/2021). [Oil mist (mineral oil particles)]

TWA: 1 mg/m³ 8 hours. Form: mineral oil particles **FOR-2011-12-06-1358 (Norway, 6/2021). [Oil vapor]** TWA: 50 mg/m³ 8 hours. Form: vapor

Reportable hazardous constituent(s) contained in UVCB and/or multi-constituent substance(s) complying

No exposure limit value known.

Biological Limit Values (BLV)

No exposure indices known.

Recommended monitoring procedures

: Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Advisory OEL

: Mineral oil mist: USA: OSHA (PEL) TWA 5 mg/m3, NIOSH (REL) TWA 5 mg/m3, STEL 10 mg/m3, ACGIH (TLV) TWA 5 mg/m3 (highly refined)

DNELs/DMELs

Product/substance	Туре	Exposure	Value	Population	Effects
☑stillates (petroleum), hydrotreated	DNEL	Long term Oral	0.74 mg/	General	Systemic
heavy paraffinic			kg bw/day	population	
	DNEL	Long term Dermal	0.97 mg/	Workers	Systemic
			kg bw/day		
	DNEL	Long term	1.19 mg/m ³	General	Local
		Inhalation		population	
	DNEL	Long term	2.73 mg/m ³	Workers	Systemic
		Inhalation			
	DNEL	Long term	5.58 mg/m ³	Workers	Local
		Inhalation			
Lubricating oils (petroleum), C15-30,	DNEL	Long term	5.4 mg/m ³	Workers	Local
hydrotreated neutral oil-based		Inhalation			
	DNEL	Long term	1.2 mg/m ³	General	Local
		Inhalation		population	

Revision:2023/10/17 Version: 1.01 Norway ENGLISH 6/20



SDS#: C3I2EIDG4

	DNEL	Long term Oral	0.74 mg/	General	Systemic
	DNEL	Long term Dermal	kg bw/day 0.97 mg/	population Workers	Systemic
	DIVLL	Long term berman	kg bw/day	Workers	Oysternic
	DNEL	Long term	1.19 mg/m³		Local
	חאבו	Inhalation	0.70 /3	population	Cyatamia
	DNEL	Long term Inhalation	2.73 mg/m ³	Workers	Systemic
	DNEL	Long term	5.58 mg/m ³	Workers	Local
		Inhalation			
Lubricating oils (petroleum), C20-50,	DNEL	Long term Inhalation	2.73 mg/m ³	Workers	Systemic
hydrotreated neutral oil-based	DNEL	Long term Oral	0.74 mg/	General	Local
			kg bw/day	population	
	DNEL	Long term	5.58 mg/m ³	Workers	Local
	DNEL	Inhalation	0.97 mg/	Workers	Systemic
	DIVEL	Long term Dermal	kg bw/day	AA OI VOI 2	Systemic
	DNEL	Long term Oral	0.74 mg/	General	Systemic
	D	1	kg bw/day	population	0
	DNEL	Long term Dermal	0.97 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term	1.19 mg/m ³	General	Local
		Inhalation		population	
	DNEL	Long term	2.73 mg/m ³	Workers	Systemic
	DNEL	Inhalation Long term	5.58 mg/m³	Workers	Local
	DIVLE	Inhalation	0.00 mg/m	Workere	Local
Distillates (petroleum), solvent-	DNEL	Long term Oral	0.74 mg/	General	Systemic
dewaxed heavy paraffinic	DNEL	Long torm Dormal	kg bw/day	population Workers	Systemia
	DINEL	Long term Dermal	0.97 mg/ kg bw/day	vvoikeis	Systemic
	DNEL	Long term	1.19 mg/m ³	General	Local
	DATE	Inhalation	0.70 / 3	population	
	DNEL	Long term Inhalation	2.73 mg/m ³	Workers	Systemic
	DNEL	Long term	5.58 mg/m ³	Workers	Local
		Inhalation			
Distillates (petroleum), solvent-	DNEL	Long term Oral	0.74 mg/		Systemic
dewaxed light paraffinic	DNEL	Long term Dermal	kg bw/day 0.97 mg/	population Workers	Systemic
		2.1.9 25 25	kg bw/day		
	DNEL	Long term	1.19 mg/m ³		Local
	DNEL	Inhalation Long term	2.73 mg/m ³	population Workers	Systemic
	21422	Inhalation	2.70 mg/m	· · · · · · · · · · · · · · · · · · ·	2,01011110
	DNEL	Long term	5.58 mg/m ³	Workers	Local
reaction mass of isomore of	DNEL	Inhalation	0.006 mg/	Workers	Local
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-	DINEL	Long term Dermal	cm ²	Workers	Local
4-hydroxyphenyl)propionate					
	DNEL	Long term Oral	0.16 mg/	General	Systemic
	DNEL	Long term Dermal	kg bw/day 0.22 mg/	population Workers	Systemic
	DINCL	Long Gill Dellial	kg bw/day	VVOINGIO	Cystoffile
	DNEL	Long term Dermal	0.33 mg/	General	Systemic
	ריבי		kg bw/day	population	Curata wai ia
	DNEL	Long term Inhalation	0.74 mg/m ³	General population	Systemic
	DNEL	Short term Dermal	1 mg/cm ²	Workers	Local
	DNEL	Long term	2.33 mg/m ³	Workers	Systemic
•	•	•	•		



SDS#: C3I2EIDG4

		Inhalation			
	DNEL	Short term Dermal	8.33 mg/ cm ²	General population	Local
	DNEL	Short term Dermal	20 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Oral	50 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	50 mg/kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	875 mg/m ³	General population	Systemic
	DNEL	Short term Inhalation	1750 mg/ m³	Workers	Systemic
Paraffin oils (petroleum), catalytic dewaxed heavy	DNEL	Long term Oral	0.74 mg/ kg bw/day	General population	Systemic
dewaxed fleavy	DNEL	Long term Dermal	0.97 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.19 mg/m³	General population	Local
	DNEL	Long term Inhalation	2.73 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	5.58 mg/m ³	Workers	Local
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	DNEL	Long term Oral	0.04 mg/ kg bw/day	General population	Systemic
products with 2,7,7 tilllothypolitons	DNEL	Long term Dermal	0.04 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.08 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	0.14 mg/m ³	General population	Systemic
	DNEL	Long term	0.6 mg/m³	Workers	Systemic
C14-16-18 Alkyl phenol	DNEL	Inhalation Long term Inhalation	1.17 mg/m³	Workers	Systemic
	DNEL	Long term Dermal	0.3 mg/kg bw/day	Workers	Systemic

PNECs

Product/ingredient name	Compartment Detail	Name	Method Detail
☑istillates (petroleum), hydrotreated heavy paraffinic	Secondary Poisoning	9.33 mg/kg	-
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Secondary Poisoning	9.33 mg/kg	-
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate	Fresh water	0.0043 mg/l	-
	Marine water	0.00043 mg/l	-
	Fresh water sediment	233 mg/kg dwt	-
	Marine water sediment	23.3 mg/kg dwt	-
	Soil	189 mg/kg	-
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	Fresh water	33.8 µg/l	-
	Marine water	3.38 µg/l	-
	Fresh water sediment	446 µg/kg dwt	-
	Marine water sediment	44.6 µg/kg dwt	-
	Soil	1.76 mg/kg dwt	-
C14-16-18 Alkyl phenol	Fresh water	0.1 mg/l	-
	Marine water	0.01 mg/l	-
	Fresh water sediment	4266.16 mg/kg dwt	-
		1	



SDS #: C3I2EIDG4

Marine water sediment 426.62 mg/kg dwt	-
Soil 852.58 mg/kg dwt	-
Sewage Treatment 100 mg/l	-
Plant	

8.2 Exposure controls

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne

contaminants.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Skin protection

: In case of contact through splashing: safety glasses with side-shields, EN 166.

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Hydrocarbon-proof gloves

nitrile rubber Fluorinated rubber

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

In case of prolonged contact with the product, it is recommended to wear gloves complying with ISO 21420 and EN 374 standards, protecting at least for 480 minutes and having a thickness of 0,38 mm at least. These values are indicative only. The level of protection is provided by the material of the glove, its technical characteristics, its resistance to the chemicals to be handled, the appropriateness

of its use and its replacement frequency

Body protection: Personal protective equipment for the body should be selected based on the task

being performed and the risks involved and should be approved by a specialist

before handling this product. Non-skid safety shoes or boots

Respiratory protection: None under normal use conditions. If these are not sufficient to maintain exposure

below the OEL, suitable respiratory protection must be worn (Type A/P1).

Environmental exposure

controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process

equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature (20°C / 68°F) and pressure (1013 hPa) unless otherwise indicated

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid.
Color : Clear.

Odor : Characteristic.

pH : Not applicable. Product is non-soluble (in water).

Melting point/freezing point: Technically not possible to

measure



SDS #: C3I2EIDG4

Initial boiling point and

boiling range

: >316°C [ISO 3405]

Flash point

: Open cup: 214 to 261°C

[ASTM D 92] : Not applicable.

Flammability

Lower and upper explosion

: Lower: 0.9%

limit

Upper: 7%

Vapor pressure

: <0.013 kPa [room temperature]

Not applicable. [50°C]

Vapor density

: >2 [Air = 1]

Relative density

: 0.765 to 0.935 [ISO 12185]

Density

water

: 0.765 to 0.935 g/cm³ [15°C] [ISO 12185]

Solubility(ies)

.

Media

Result

Not soluble

Miscible with water

: No.

water

Partition coefficient: n-octanol/ : Not applicable.

Auto-ignition temperature

: >261°C [ASTM E 659]

Decomposition temperature

: Not applicable.

Viscosity

: Kinematic (40°C): 58.5 to 71.5 mm²/s [ISO 3104]

Particle characteristics

Median particle size

: Not applicable.

9.2 Other information

No other relevant physical and chemical parameters for the safe use of the product

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : Stable under recommended storage and handling conditions (see Section 7).

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

10.5 Incompatible materials : Strong oxidizing agents

10.6 Hazardous

decomposition products

: carbon monoxide carbon dioxide nitrogen oxides phosphorus oxides sulfur oxides Hydrogen sulfide Mercaptans



SDS #: C3I2EIDG4

Zinc oxides

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/substance	Result	Species	Dose	Exposure	Test
Distillates (petroleum),	LC50 Inhalation Dusts	Rat - Male,	>5 mg/l	4 hours	OECD 403
hydrotreated heavy paraffinic	and mists	Female	· ·		Read across
	LD50 Dermal	Rabbit - Male,	>5000 mg/kg	-	OECD 402
		Female			Read across
	LD50 Oral	Rat - Male,	>5000 mg/kg	-	OECD 401
		Female			Read across
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	LC50 Inhalation Dusts and mists	Rat	5.53 mg/l	4 hours	OECD 403
	LD50 Dermal	Rabbit	>5000 mg/kg	_	OECD 402
	LD50 Oral	Rat	>5000 mg/kg	-	OECD 401
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	LC50 Inhalation Dusts and mists	Rat	5.1 mg/l	4 hours	OECD 403
Trodital oil based	LD50 Dermal	Rabbit - Male, Female	>5000 mg/kg	-	OECD 402 Read across
	LD50 Oral	Rat - Male, Female	>5000 mg/kg	-	OECD 401 Read across
Distillates (petroleum), solvent-dewaxed heavy paraffinic	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours	OECD 403
paramine	LD50 Dermal	Rabbit	>5000 mg/kg	_	OECD 402
	LD50 Oral	Rat	>5000 mg/kg	_	OECD 420
Distillates (petroleum), solvent-dewaxed light paraffinic	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours	OECD 403
paramino	LD50 Dermal	Rabbit	>5000 mg/kg	_	OECD 402
	LD50 Oral	Rat	>5000 mg/kg	_	OECD 401
Paraffin oils (petroleum), catalytic dewaxed heavy	LC50 Inhalation Dusts and mists	Rat	5.1 mg/l	4 hours	-
cataly as demands nearly	LC50 Inhalation Vapor	Rat	80.4 mg/l	1 hours	_
	LC50 Inhalation Vapor	Rat	20.1 mg/l	4 hours	_
	LD50 Dermal	Rabbit	>5000 mg/kg	-	-
	LD50 Oral	Rat	>5000 mg/kg	_	-
Benzenamine, N-phenyl-,	LD50 Oral	Rat	>2500 mg/kg	-	-
reaction products with					
2,4,4-trimethylpentene					
C14-16-18 Alkyl phenol	LD50 Dermal	Rat	2000 mg/kg	-	-
	LD50 Oral	Rat	2000 mg/kg	-	-

Acute toxicity estimates

Product/substance	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	N/A	N/A	N/A	N/A	5.53
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	N/A	N/A	N/A	N/A	5.1
Paraffin oils (petroleum), catalytic dewaxed heavy	N/A	N/A	N/A	20.1	5.1

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Revision:2023/10/17 Version: 1.01 **ENGLISH** 11/20 Norway



SDS#: C3I2EIDG4

Irritation/Corrosion

Conclusion/Summary

Skin
 Based on available data, the classification criteria are not met.
 Eyes
 Based on available data, the classification criteria are not met.
 Respiratory
 Based on available data, the classification criteria are not met.

Sensitization

Conclusion/Summary

Skin: Based on available data, the classification criteria are not met. Contains sensitizer.

May produce an allergic reaction.

Respiratory: Based on available data, the classification criteria are not met.

Mutagenicity

Conclusion/Summary: Based on available data, the classification criteria are not met.

Carcinogenicity

Product/substance	Result	Species	Dose	Exposure
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert- butyl-4-hydroxyphenyl) propionate	Negative - Oral - TC	Rat - Male, Female	-	-

Conclusion/Summary: Based on available data, the classification criteria are not met.

Reproductive toxicity

Conclusion/Summary: Based on available data, the classification criteria are not met.

Teratogenicity

Conclusion/Summary: Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Conclusion/Summary: Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure)

Product/substance	Category	Route of exposure	Target organs
C14-16-18 Alkyl phenol	Category 2	-	-

Conclusion/Summary: Based on available data, the classification criteria are not met.

Aspiration hazard

Product/substance	Result
vistillates (petroleum), hydrotreated heavy paraffinic	ASPIRATION HAZARD - Category 1
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-	ASPIRATION HAZARD - Category 1
based	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-	ASPIRATION HAZARD - Category 1
based	
Distillates (petroleum), solvent-dewaxed heavy paraffinic	ASPIRATION HAZARD - Category 1
Distillates (petroleum), solvent-dewaxed light paraffinic	ASPIRATION HAZARD - Category 1
Paraffin oils (petroleum), catalytic dewaxed heavy	ASPIRATION HAZARD - Category 1

Conclusion/Summary: Based on available data, the classification criteria are not met.

Information on the likely

routes of exposure

: Not available.

Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.



SDS #: C3I2EIDG4

Skin contact: Defatting to the skin. May cause skin dryness and irritation.

Ingestion: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

irritation dryness cracking

Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : N

: Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary: Not available.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACh Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/substance	Result	Species	Exposure	Test
☑istillates (petroleum), hydrotreated heavy paraffinic	Acute EC50 >100 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours	OECD 201
	Acute EC50 >10000 mg/l	Crustaceans - Daphnia magna	48 hours	OECD 202
	Chronic NOEL >100 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours	OECD 201
	Chronic NOEL >1000 mg/l	Crustaceans - Daphnia	21 days	-



SDS#: C3I2EIDG4

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	Acute EL50 >100 mg/l	magna Algae - Pseudokircheriella subcapitata	72 hours	OECD 201
	Acute EL50 >10000 mg/l	Crustaceans - Daphnia magna	48 hours	OECD 202
	Acute LL50 >1000 mg/l	Fish - Pimephales promelas	96 hours	OECD 203
	Chronic NOEL >100 mg/l	Algae - Pseudokircheriella subcapitata	72 hours	OECD 201
	Chronic NOEL >1000 mg/l	Crustaceans - Daphnia magna	21 days	OECD 211
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	Acute EL50 >100 mg/l	Algae - Pseudokirchneriella subcapitata	48 hours	OECD 201
	Acute EL50 >10000 mg/l	Crustaceans - Daphnia magna	48 hours	OECD 202
	Acute LL50 >100 mg/l	Fish - Pimephales promelas	96 hours	OECD 203
	Chronic NOEL >100 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours	OECD 201
	Chronic NOEL >1000 mg/l	Crustaceans - Daphnia magna	21 days	OECD 211
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Acute EL50 >10000 mg/l	Crustaceans - Daphnia magna	48 hours	OECD 202
	Acute LL50 >1000 mg/l	Fish - Oncorhynchus mykiss	96 hours	OECD 203
	Chronic NOEL >1000 mg/l	Crustaceans - Daphnia magna	21 days	OECD 211
Distillates (petroleum), solvent-dewaxed light paraffinic	Acute EL50 >100 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours	OECD 201
paramino	Acute EL50 10000 mg/l	Crustaceans - Daphnia magna	48 hours	OECD 202
	Acute EL50 ≥100 mg/l	Fish - Pimephales promelas	96 hours	OECD 203
	Chronic NOEL >100 mg/l	Algae - Pseudokirchneriella	72 hours	OECD 201
	Chronic NOEL >1000 mg/l	subcapitata Crustaceans - Daphnia magna	21 days	OECD 211
Paraffin oils (petroleum), catalytic dewaxed heavy	Acute EC50 10000 mg/l	Daphnia	48 hours	-
catalytic dewaxed fleavy	Acute NOEL 101 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours	-
C14-16-18 Alkyl phenol	Acute EC50 >100 mg/l	Daphnia - <i>Daphnia magna</i>	48 hours	OECD 202

Conclusion/Summary: Not available.

12.2 Persistence and degradability



SDS #: C3I2EIDG4

Product/substance	Test	Result	Dose	Inoculum
istillates (petroleum), hydrotreated heavy paraffinic	OECD 301F	31 % - Not readily - 28 days	-	Activated sludge
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	OECD 301F	31 % - Not readily - 28 days	-	Activated sludge
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	OECD 301F	31 % - Not readily - 28 days	-	Activated sludge
Distillates (petroleum), solvent-dewaxed heavy paraffinic	OECD 301F	31 % - Not readily - 28 days	-	Activated sludge
Distillates (petroleum), solvent-dewaxed light paraffinic	OECD 301F	31 % - Not readily - 28 days	-	Activated sludge
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert- butyl-4-hydroxyphenyl) propionate	OECD 301B	2 % - Not readily - 28 days	-	Activated sludge

Conclusion/Summary: Not available.

Product/substance	Aquatic half-life	Photolysis	Biodegradability
Distillates (petroleum),	-	-	Not readily
hydrotreated heavy paraffinic Lubricating oils (petroleum), C15-30, hydrotreated	-	-	Not readily
neutral oil-based Lubricating oils (petroleum), C20-50, hydrotreated	-	-	Not readily
neutral oil-based Distillates (petroleum), solvent-dewaxed heavy	-	-	Not readily
paraffinic Distillates (petroleum), solvent-dewaxed light	-	-	Not readily
paraffinic reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert- butyl-4-hydroxyphenyl)	-	-	Not readily
propionate Paraffin oils (petroleum), catalytic dewaxed heavy	-	-	Not readily
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	-	-	Not readily

12.3 Bioaccumulative potential

Product/substance	LogK _{ow}	BCF	Potential
istillates (petroleum), hydrotreated heavy paraffinic	>4	-	High
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based		-	High
Distillates (petroleum), solvent-dewaxed heavy paraffinic	9.2	260	Low
Distillates (petroleum), solvent-dewaxed light	3.1	-	Low



otalEnergies sps #: C3l2ElDG4

paraffinic reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-	9.2	260	Low
butyl-4-hydroxyphenyl) propionate			
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	5.1	1730	High

12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Mobility

: Not available.

Mobility in soil

: Given its physical and chemical characteristics, the product generally shows low soil mobility. The product is insoluble and floats on water. Loss by evaporation is limited

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB in a concentration >= 0,1 %.

12.6 Endocrine disrupting properties

This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACh Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste

: Yes.

According to the European Waste Catalogue, Waste Codes are not product specific, but application specific Waste codes should be assigned by the user based on the application for which the product was used. The following Waste Codes are only suggestions: 13 02 05*

Packaging

Methods of disposal

: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions

: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.



SDS #: C3I2EIDG4

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ICAO/IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

14.7 Maritime transport in

bulk according to IMO

instruments

: Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Other EU regulations

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Industrial emissions

: Not listed

(integrated pollution prevention and control) -

Industrial emissions

: Not listed

(integrated pollution prevention and control) -

Water

Explosive precursors : Not applicable. Ozone depleting substances (1005/2009/EU)

Not listed.

Revision:2023/10/17 Version: 1.01 **ENGLISH** 17/20 Norway



SDS #: C3I2EIDG4

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

LU - Luxembourg prohibited chemicals in the workplace

Not listed.

Inventory list

Australia inventory (AIIC)

Canada inventory (DSL/NDSL)

China inventory (IECSC)

Europe inventory (EC)

: All components are listed or exempted.

All components are listed or exempted.

All components are listed or exempted.

Japan inventory : Japan inventory (CSCL): All components are listed or exempted.

Japan inventory (ISHL): All components are listed or exempted.

New Zealand Inventory of Chemicals (NZIoC)

Philippines inventory (PICCS)

Korea inventory (KECI)

Taiwan Chemical Substances Inventory (TCSI)

Thailand inventory Turkey inventory

United States inventory (TSCA 8b)

Vietnam inventory

: All components are listed or exempted.

: All components are listed or exempted.

: MI components are listed or exempted.

: MI components are listed or exempted.

: Not determined.

: Not determined.

: All components are listed or exempted.

: Not determined.



SDS #: C312EIDG4

The information stated in this section relates solely to the conformity of the chemical product with the countries Inventories. The information used to confirm the inventory status of this product may be based on additional data to the chemical composition shown in Section 3. Other regulations may apply for importation or marketing authorizations.

15.2 Chemical Safety

: Risk management measures and safety conditions of use are included in the

Assessment relevant sections of the SDS

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ACGIH = American Conference of Governmental Industrial Hygienists

ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DNEL = Derived No Effect Level
DMEL = Derived Minimal Effect Level
EL50 = median Effective Loading

EUH statement = CLP-specific Hazard statement

LC50 = Median lethal concentration

LD50 = Median lethal dose

N/A = Not available

NIOSH = National Institute of Occupational Safety and Health

NOAEL = No Observed Adverse Effect Level NOEC No Observed Effect Concentration OEL = Occupational Exposure Limit

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration

QSAR = Quantitative Structure–Activity Relationship

REL = Recommanded Exposure Limit STEL = Short Term Exposure Limit TLV = Threshold Limit Value

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Unique Formula Identifier (UFI)

UVCB Substance of unknown or Variable composition, Complex reaction products

or Biological material

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Not classified.	

Full text of abbreviated H statements

⊮ 304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated
	exposure.
H413	May cause long lasting harmful effects to aquatic life.

Full text of classifications [CLP/GHS]

Aquatic Chronic 4	AQUATIC HAZARD (LONG-TERM) - Category 4
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Repr. 2	TOXIC TO REPRODUCTION - Category 2
Skin Sens. 1B	SKIN SENSITIZATION - Category 1B
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY (REPEATED
	EXPOSURE) - Category 2

 Revision:2023/10/17
 Version : 1.01
 Norway
 ENGLISH
 19/20



SDS #: C3I2EIDG4

Date of revision: 2023/10/17previous revision date: 2023/07/19

Version : 1.01

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.